

Pressure Washer, Single Phase

Totally Enclosed Fan Cooled



Features:



- Ball bearings, shaft end mechanically locked on C-face models
- Heavy gauge steel constructions
- Capacitor start/capacitor run design for higher efficiency, as noted
- Continuous duty, 1.15 Service Factor
- Manual reset thermal protector
- UL Recognized and CSA Certified

Rigid Base

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
3/4	3600	115/208-230	56	G379	56C34F5309	★	\$259	F1	10.6/5.3-5.3	12.32	2,14
	1800	115/208-230	56	G356	56C17F5308	★	\$357	F1	11.0/5.4-5.5	12.32	2,14
1	3600	115/208-230	56	G390	56C34F5311	★	\$293	F1	12.4/6.7-6.2	12.32	2,14
	1800	115/208-230	56	G373	56C17F5311	★	\$374	F1	13.4/6.8-6.7	12.82	2,14
1 1/2	3600	115/208-230	56	K332	56B34F5303		\$397	F1	12.1/6.9-6.1	13.32	1,14
	1800	115/208-230	56H	G378	56B17F5302	★	\$429	F1	15.2/8.2-7.6	13.82	1,5,14
2	1800	115/230	145T	I702	145TBFR5336		\$550	S1	18.8/9.4	14.87	1,14

C-Face with Rigid Base

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/2	1800	115/208-230	56C	G380	56C17F5957		\$330	F1	8.8/4.2-4.4	11.82	2
3/4	1800	115/208-230	56C	G381	56C17F5955	★	\$395	F1	11/5.4-5.5	12.32	2
1	1800	115/208-230	56C	G382	56C17F5956	★	\$413	F1	13.4/6.8-6.7	12.82	2
1 1/2	3600	115/208-230	56C	K612	56B34F5306	★	\$412	F1	12.1/6.9-6.0	13.32	1
	1800	115/208-230	56HC	G396	56B17F5310	★	\$471	F1	13.6/7.5-6.8	13.82	1,5
2	3600	115/230	56HC	K615	56B34F5312	★	\$489	F1	17.5/8.7	13.32	1,5
	1800	115/230	145TC	I311	145TBFR5333		\$666	S1	18.8/9.4	14.87	1
	1800	115/230	56HC	K319	56B17F5319	★	\$559	F1	18.8/9.4	14.82	1,5
3	3600	230	56HC	K618	56B34F5318	★	\$617	F1	11.8	14.82	1,5
	1800	230	184TC	I314	184TBFR7041	★	\$838	S1	13.7	17.61	d,1
	1800	230	184TC	I1314	184TBF7041	★	\$838	S1	12.8	14.96	1,13
5	1800	230	184TC	I315	184TBFR7034	★	\$1,000	S1	21.0	18.72	d,1,17
	1800	230	184TC	I1315	184TBF7034	★	\$1,000	S1	19.5	17.47	1,13,17