

**200 Volt,
Three Phase,
TEFC, Foot Mounted**

1/2 thru 50 Hp

NEMA 56C thru 326T

Applications: Pumps, fans, compressors, blowers, machine tools, conveyors and many other applications requiring 200 volt power.

Features: 1.15 Service Factor, positively locked drive end bearing on 254T and larger, ball bearings, dynamically balanced rotors. EM Super-E® motors have NEMA Premium® efficiency and 3 year warranty.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
Foot Mounted												
1	1800	143T	EM3546T-8	641	L1	13.31	39	85.5	200	3.5	B	1, 30, 68
		143T	M3546T-8	434	L1	12.31	28	82.5	200	4	B	68
1 1/2	1800	145T	EM3554T-8	666	L1	14.19	48	86.5	200	4.8	B	1, 30, 68
		145T	M3554T-8	443	L1	12.31	36	84	200	6.2	B	68
2	1800	145T	EM3558T-8	690	L1	14.19	49	86.5	200	6.3	B	1, 30, 68
		145T	M3558T-8	465	L1	13.31	43	84	200	7	B	68
3	3600	182T	EM3660T-8	990	L1	15.24	89	86.5	200	7.8	B	1, 30, 68
		182T	EM3661T-8	1,018	L1	15.24	91	89.5	200	9.1	B	1, 30, 68
		182T	M3611T-8	550	L1	15.14	53	87.5	200	9.4	B	1, 68
5	3600	184T	EM3663T-8	1,218	L1	15.24	97	88.5	200	13	B	1, 30, 68
		184T	EM3665T-8	1,019	L1	15.24	109	89.5	200	14.9	B	1, 30, 68
		184T	M3615T-8	633	L1	16.55	74	87.5	200	15.2	B	1, 68
7 1/2	3600	213T	EM3769T-8	1,410	L1	18.45	173	89.5	200	19.8	B	1, 68
		213T	EM3770T-8	1,358	L1	18.45	170	91.7	200	21.4	B	1, 68
		213T	M3710T-8	808	L1	17.89	113	89.5	200	23.2	B	1, 68
10	3600	215T	EM3771T-8	1,653	L1	18.45	203	90.2	200	26.5	B	1, 30, 68
		215T	EM3774T-8	1,525	L1	18.45	231	91.7	200	28.4	B	1, 30, 68
		215T	M3714T-8	981	L1	19.01	127	89.5	200	31.3	B	2, 20, 68
15	3600	254T	EM2394T-8	2,276	L1	23.16	267	91	200	40	B	1, 30, 68
		254T	EM2333T-8	2,094	L1	23.16	238	92.4	200	42.4	B	1, 30, 68
		254T	M2333T-8	1,722	L1	21.07	222	91	200	42.5	B	1, 68
20	3600	256T	EM4106T-8	2,499	L1	23.16	285	91	200	52	B	1, 24, 30, 69
		256T	EM2334T-8	2,540	L1	23.16	286	93	200	55.2	B	1, 24, 30, 69
		256T	M2334T-8	2,078	L1	23.28	261	91	200	55	B	1, 24, 69
25	3600	284TS	EM4107T-8	3,260	L1	25.70	382	91.7	200	65	B	1, 24, 69
		284T	EM4103T-8	3,321	L1	27.76	407	93.6	200	68.4	B	1, 24, 69
		284T	M4103T-8	2,570	L1	26.08	361	92.4	200	67	B	1, 24, 69
30	3600	286TS	EM4108T-8	3,875	L1	24.70	407	91.7	200	76	B	1, 24, 69
		286T	EM4104T-8	3,941	L1	27.76	426	93.6	200	84	B	1, 24, 69
		286T	M4104T-8	3,036	L1	26.08	386	92.4	200	83	B	1, 24, 69
40	1800	324T	EM4110T-8	5,154	L1	30.28	604	94.1	200	111	B	1, 24, 69
		324T	M4110T-8	4,028	L1	30.39	522	93	200	108	B	1, 24, 69
50	1800	326T	EM4115T-8	5,632	L1	30.28	632	94.5	200	131	B	1, 24, 69
		326T	M4115T-8	4,170	L1	30.39	554	93	200	137	B	1, 24, 69
C-Face, Foot Mounted												
1/2	1800	56C	CM3538-8	417	K	11.35	23	74	200	2.2	C	
1	1800	56C	CM3546-8	421	K	12.00	29	78.5	200	3.9	C	

(a) See notes on inside back flap.

■ Cast Iron Frame

Farm Duty Motors

Definite Purpose Motors

Unit Handling Motors

Brake Motors

200 & 575 Volt Motors

IEC Frame Motors

50 Hertz Motors

Inverter/Vector Motors & Controls

DC Motors and Controls

Soft Starters & Dynamic Brakes