

## Accessories for testo 175 and 177

### testo 575 fast printer

- Fast-action print mechanism, 6 lines/s
- Prints tables/graphics
- Brief info. or full memory can be printed as required
- Determine section to be printed
- Your language can be set
- Self-adhesive Testo paper can also be used



Fast printout and logger rebooting with testo 575

Part no. 0554 1775

### testo 581 alarm signal output

- Transmission of alarm messages – e.g. when programmed limit values in the datalogger are exceeded – to external components such as horns, lamps, PLC etc.
- Signal transfer via floating signal output



Alarm signal output for reliable indication of limits exceeded

Part no. 0554 1769

### testo 580 data collector

- Can read out up to 25 full testo 175 loggers or 10 full testo 177 loggers
- Displays all status information
- Download collected data to PC using Testo ComSoft 3



The testo 580 data collector collects data on site for upload to PC and analysis

Part no. 0554 1778

### Ethernet adapter

- Fast transfer of readings
- Use of an existing network without additional cabling
- Long transmission paths
- Identification of measuring instruments in system network
- In connection with ComSoft 3



Read out the data stored in the logger via the PC network using the Ethernet adapter

Part no. 0554 1711

Printer and Accessories	Part no.
Fast testo 575 printer, incl. 1 roll of thermal paper and batteries, Infrared thermal line printer with graphics function	0554 1775
Spare thermal paper for printer, built-in in testo 314 (6 rolls)	0554 0569
Spare thermal paper for printer (6 rolls), Measurement data documentation legible for up to 10 years	0554 0568
Label thermal paper (Testo patent) for testo 575 printer (6 rolls), can be applied directly	0554 0561
Additional accessories	Part no.
testo 580 data collector including readout holders, For testo 175/177 dataloggers	0554 1778
testo 581 alarm signal output, floating, for testo 175/177, Forwards information efficiently when limits are exceeded to e.g. horns, lamps, PLC etc.	0554 1769
Battery, 3.6 V/0.8 Ah 1/2 AA, for testo 175-T3/175-H1/175-H2/175-S1	0515 0175
Battery, 3.6 V/1.9 Ah 1AA, for testo 175-T1/175-T2 and all testo 177 loggers	0515 0177
Transport and protection	Part no.
Lock for wall holder for testo 175/177 dataloggers	0554 1755
Transport case for up to 5 testo 175 dataloggers, testo 575 printer, testo 580 data collector and accessories	0516 1750
Transport case for up to 5 testo 177 dataloggers, testo 575 printer, testo 580 data collector and accessories	0516 1770
Accessories for humidity probes	Part no.
Control and humidity adjustment set 11.3%RH/75.3%RH incl. adapter for humidity probes, Quick checks or calibration of humidity probe	0554 0660
Metal protection cage, Ø 12 mm for humidity probes, For velocities of less than 10 m/s	0554 0755
Cap with wire mesh filter, Ø 12 mm	0554 0757
Teflon sintered filter, Ø 12 mm, for corrosive substances, High humidity range (long-term measurements), high velocities	0554 0756
Stainless steel sintered cap, Ø 12 mm, is screwed onto humidity probe, For measurements at high velocity speeds or in dirt ingressed air	0554 0647

Software and Accessories	Part no.
<b>For testo 175:</b> ComSoft 3 Set - Basic with RS 232 interface, Basic software with diagram and table function, incl. desk-top holder, PC connection cable	0554 1759
<b>For testo 175:</b> ComSoft 3 Set - Basic with USB interface, Basic software with diagram and table function, incl. desk-top holders, PC connection cable	0554 1766
<b>For testo 177:</b> ComSoft 3 Set - Basic with RS 232 interface, Basic software with diagram and table function, incl. desk-top holder, PC connection cable	0554 1774
<b>For testo 177:</b> ComSoft 3 Set - Basic with USB interface, Basic software with diagram and table function, incl. desk-top holders, PC connection cable	0554 1767
ComSoft 3 - Professional with data management, Incl. database, analysis and graphics function, data analysis, trend curve (without interface)	0554 0830
ComSoft 3 - For requirements to CFR 21 Part 11, Incl. database, analysis and graphics function, data analysis, trend curve	0554 0821
RS 232 interface for testo 175/177 incl. desk-top holders, PC connection cable, (please also order for ComSoft 3 - Professional)	0554 1757
USB interface, for testo 175/177 incl. desk-top holders, PC conn. cable, (Please order with ComSoft 3 - Professional)	0554 1768
Ethernet adapter, RS 232 - Ethernet incl. software driver, mains unit, Facilitates data communication in network	0554 1711
Calibration Certificates	Part no.
ISO calibration certificate/Temperature, Temp. datalogger; calibration points -18°C; 0°C; +60°C per channel/instrument	0520 0151
ISO calibration certificate/Temperature, Temp. datalogger; calibration points -8°C; 0°C; +40°C per channel/instrument	0520 0171
ISO cal. cert./Humidity, Humidity datalogger; calibration points 11.3%RH and 75.3%RH at +25°C; per channel/instrument	0520 0076
DKD calibration certificate/Temperature, Temp. datalogger; cal. points -20°C; 0°C; +60°C; per channel/instrument	0520 0261
DKD calibration cert./Humidity, Humidity datalogger; cal. points 11.3%RH and 75.3%RH at +25°C; per channel/instrument	0520 0246