

Penetration thermometer – Fast and robust

testo 106

The testo 106 penetration thermometer, with its thin, robust measurement tip is ideal for quick core temperature checks.

testo 106-T1

Penetration thermometer incl. probe protection cap and battery

Part no. 0560 1061

Accessories Ordering data	Part no.
Frozen food drill, Can be attached to holder clip	0554 0826
TopSafe (indestructible protection case), Waterproof and dishwasher-safe protection case (IP67)	0516 8265
Holder clip with probe protection cap	0554 0825
ISO calibration certificate/Temperature, For air/immersion probes, calibration point +60°C	0520 0063
ISO calibration certificate/Temperature, For air/immersion probes, calibration point -18°C	0520 0061
ISO calibration certificate/Temperature, For air/immersion probes, calibration point 0°C	0520 0062
ISO calibration certificate/Temperature, For air/immersion probes, calibration points -18°C; 0°C	0520 0041
ISO calibration certificate/Temperature, For air/immersion probes, calibration points -8°C; 0°C; +40°C	0520 0181

testo 106-T1 Set

Penetration thermometer incl. TopSafe (water-proof protection case, IP67), positioning clip, probe protection cap and battery

Part no. 0563 1061

testo 106-T2 Set with alarm

Penetration thermometer with alarm, incl. TopSafe (water-tight protection case, IP67), positioning clip, probe protection cap and battery

Part no. 0563 1062


Small and practical, always at hand

Included:

- 1 TopSafe
- 2 Probe protection cap
- 3 Practical holding clip
- 4 Frozen food drill

Technical data

Meas. range	-50 to +230 °C		
Accuracy	±1% of mv (+100 to +230 °C) ±1 digit	±1 °C (-50 to -30.1 °C) ±0.5 °C (-30 to +99.9 °C)	
Resolution	0.1 °C	Battery life	250 h
Oper. temp.	-20 to +50 °C	Dimensions	215 x 34 x 19 mm
Storage temp.	-40 to +70 °C	Weight	80 g



Checks the right temperature in sensitive food, e.g. fish

Robust one-hand thermometer – With interchangeable measurement tips

testo 105

The robust food thermometer with interchangeable measurement tips for monitoring purposes in abattoirs, refrigerated rooms,...

- 2 user-defined limit values, alarm visual or audible
- Built-in backlit display
- Audible key feedback
- 2 line display
- Waterproof (IP 65) and robust

testo 105

One-hand thermometer with standard measurement tip, incl. battery

Part no. 0563 1051

Technical data

Sensor	NTC
Meas. range	-50 to +275 °C
Accuracy	±0.5 °C (-20 to +100 °C) ±1 digit ±1 °C (-50 to -20.1 °C) ±1 % (+100.1 to +275 °C)
Resolution	0.1 °C
Storage temp.	-40 to +70 °C
Oper. temp.	-20 to +50 °C
Protection class	IP65
Dimensions	145 x 38 x 195 mm
Weight	139 g

Accessories Ordering data

Standard measurement tip, 100 mm long

Part no. 0613 1051

Frozen food tip, 90 mm long

Part no. 0613 1052

Long measurement tip, 200 mm long


Part no. 0613 1053

Aluminium case for the testo 105 one-hand thermometer and accessories

Part no. 0554 1051

ISO calibration certificate/Temperature, For air/immersion probes, calibration points -18°C; 0°C

Part no. 0520 0041



- 1 Standard measurement tip 100 mm
- 2 Frozen food tip 90 mm
- 3 Long measurement tip 200 mm

Easy-to-change measurement tips



Penetration temperature measurement prior to further processing

Complete case

One-hand thermometer with standard measurement tip, frozen food tip, long measurement tip and belt/wall holder in aluminium case

Part no. 0563 1052