## **CONCRETE INSERTS & ATTACHMEN**

## Fig. 49

## **Concrete Clevis Plate**


Size Range: 3/8" through 13/4"


Material: Carbon steel Finish: Plain or Galvanized

Service: Structural attachment to concrete ceiling where flexibility is desired. Concrete clevis plate is normally used in conjunction with Fig. 290, page 93, weldless eye nut, or Fig. 278, page 89 welded eye rod and anchors of sufficient strength to hold the desired load.

Ordering: Specify rod size, figure number, name and finish. **Note:** Sizes <sup>3</sup>/<sub>8</sub>" through 1" are supplied with bolt and nut. Larger sizes are supplied with pin and cotters.










	FIG. 49: LOAD (LBS) • WEIGHT (LBS) • DIMENSIONS (IN)														
Rod Size A	Max Load ■	Weight	J	В	С	D	F	G	Н	R	S	Т	U	W	
3/8	730	11.8	1	8	10	5	9/16	3/8	2	7/8	11/4	1/4	1/2	2	
1/2	1,350	11.9											5/8		
5/8	2,160	15.7						1/2					3/4		
3/4	3,230	16.9					11/16			11//8	17/8	3/8	7/8	21/2	
7/8	4,480	18.1							3	11/4	2		1		
1	5,900	36.9	2		12	6	13/16	3/4	3	11/2	2½	1/2	11//8	3	
11/4	9,500	40.9					15/16			2		5/8	13/8	4	
1½	13,800	59.8					11/8	1	4	21/2	3	3/4	15/8	T _	
13/4	18,600	93.6		10	14	7	13/8	11/4	5	23/4	3½	1/2	<b>1</b> 7// <sub>8</sub>	5	

<sup>■</sup> Based on the rod diameter only. Rating is subject to the conditions that the concrete and anchors used are of sufficient strength to hold the load.



Pictorial Table of Contents

Copper Tubing Hangers

CPVC Pipe Hangers

Pipe Rings

Rod Attachments

Bolts, Nuts, Pins & U-Bolts