

BALL VALVE • FULL PORT • 600 PSI

FORGED BRASS



- 600 PSI Non-Shock WOG (1/4" through 3")
- 150 PSI WSP Steam
- Meets NSF approved low lead standards (1/2" through 2")
- CSA 3-88 (5 PSIG) Certified (1/4" through 2")
- CSA Z21-15a-90 (1/2 PSIG) Certified (2 1/2", 3")
- CSA Tamper Proof (T) (1/2" through 2")
- CSA Certified – Canadian Standards Association
- UL – L.P. Gas – 400 PSI
- Suitable for vacuum use up to 7 PSI
- Meets federal specification WW-V-35B, Type II, Style 3
- Suitable for use with flammable liquid (1/2" through 2" IPS)
- Available in Handy Carton (HC) bin box packaging
- 107-703-708/703HC-708HC/503-508 are cubic ball valves

Part No.	UPC-A (032888)	Valve Size	Port Size	CV Rating	Inner/Master Carton Qty.	Master Weight (lbs.)
Threaded						
107-701	077010	1/4"	.315"	7.7	20/200	33
107-702	077027	3/8"	.394"	7.8	10/100	29
107-703	077034	1/2"	.590"	14.2	10/100	47
107-704	077041	3/4"	.787"	28.6	10/100	71
107-705	077058	1"	.984"	56.4	10/50	48
107-706	077065	1-1/4"	1.260"	114.0	10/20	31
107-707	077072	1-1/2"	1.575"	162.9	4/20	48
107-708	077089	2"	1.968"	245.6	4/20	74
107-709	077096	2-1/2"	2.283"	279.3	2/12	43
107-710	077102	3"	2.677"	313.1	2/4	37
107-711*	077119	4"	3.543"	536.6	1/2	30
107-701HC	077010	1/4"	.315"	7.7	40/NA	6
107-702HC	077027	3/8"	.394"	7.8	40/NA	11
107-703HC	077034	1/2"	.590"	14.2	40/NA	18
107-704HC	077041	3/4"	.787"	28.6	25/NA	18
107-705HC	077058	1"	.984"	56.4	20/NA	22
107-706HC	077065	1-1/4"	1.260"	114.0	15/NA	23
107-707HC	077072	1-1/2"	1.575"	162.9	8/NA	19
107-708HC	077089	2"	1.968"	245.6	4/NA	16

Solder

107-503	075030	1/2"	.590"	14.2	10/100	38
107-504	075047	3/4"	.787"	28.6	10/60	39
107-505	075054	1"	.984"	56.4	6/36	34
107-506	075061	1-1/4"	1.260"	114.0	4/24	31
107-507	075078	1-1/2"	1.575"	162.9	4/16	34
107-508	075085	2"	1.968"	245.6	2/10	39
107-509	075092	2-1/2"	2.283"	279.3	2/6	39
107-510	075108	3"	2.677"	313.1	2/4	36

* 400 PSI rated

BALL VALVE • FULL PORT • 600 PSI

CHROME PLATED FORGED BRASS



- 600 PSI Non-Shock WOG (1/8" through 3")
- 150 PSI WSP Steam
- Meets NSF approved low lead standards (1/2" through 2")
- CSA 3-88 (5 PSIG) Certified (1/2" through 2")
- CSA Tamper Proof (T)
- CSA Certified – Canadian Standards Association
- CSA B16.33 (125 PSIG) Certified (1/2" through 1")
- UL – L.P. Gas – 400 PSI
- Meets Federal Specification WW-V-35B, Type II, Style 3
- Suitable for use with flammable liquid (1/2" through 2" IPS)
- 107-003/008 are cubic ball valves
- Threaded ends comply with ANSI B1.20.1
- -40°F to 350°F temperature range

Part No.	UPC-A (032888)	Valve Size	Port Size	CV Rating	Inner/Master Carton Qty.	Master Weight (lbs.)
Threaded						
107-000	070004	1/8"	.315"	7.2	20/200	36
107-001	070011	1/4"	.315"	7.7	20/200	25
107-002	070028	3/8"	.394"	7.8	10/100	29
107-003	070035	1/2"	.590"	14.2	10/100	46
107-004	070042	3/4"	.787"	28.6	10/100	72
107-005	070059	1"	.984"	56.4	10/50	56
107-006	070066	1-1/4"	1.260"	114.0	10/20	31
107-007	070073	1-1/2"	1.575"	162.9	4/20	48
107-008	070080	2"	1.968"	245.6	4/20	80