

WHEATLAND TUBE **WT-ColorCoat** FENCE FRAMEWORK


FOUR LAYERS OF PROTECTION ENHANCED WITH COLOR

Galvanized coating + intermediate conversion coating
+clear polymer coating + polyester WT-ColorCoat

Attractive..Affordable.. Durable..Dependable..Value



Wheatland's 3 mil Polyester TGIC Powder WT-ColorCoat meets or exceeds the coating requirements of ASTM F 1043 "Standard Specification for Strength and Protective Coatings on Steel Industrial Chain Link Fence Framework"



WT-ColorCoat dark green and black colors are in compliance with ASTM F 934 "Standard Specification for Standard Colors for Polymer-Coated Chain Link Fence Materials"

Specifications Polyester TGIC Powder coating ASTM F 1043

Thickness: 3 mils [0.0076 mm]	Adhesion: Compliance with cross hatch test ASTM D 3359
Color: ASTM F 934	Gloss : (60°) 60-70, ASTM D 523
Pencil Hardness : 2H, ASTM D 3363	Impact : 160+inch pounds , ASTM D 2794
Weathering: 1000 hours, ASTM D 1499 weatherometer	

WT-ColorCoat is available with:
WT-40.....WT-30.....WT-20.....WT-15.....
Tubing Wall 0.065 -- 0.055



Wheatland Tube Company 700 South Dock Street, Sharon, PA 16146
 Phone: 800-343-0124 Fax: 888-246-0457 www.wheatland.com

WHEATLAND TUBE **WT-ColorCoat** FENCE FRAMEWORK

Product	Fence O.D.	Decimal Equivalent	Wall Thickness	Gauge	Weight lbs/ft	Pieces Lift
Residential	1-3/8	1.315	.055	17	0.74	91
Residential	1-3/8	1.315	.065	16	0.87	91
WT-15	1-3/8	1.315	.072	15	0.96	91
Residential	1-5/8	1.660	.055	17	0.94	61
Residential	1-5/8	1.660	.065	16	1.11	61
WT-15	1-5/8	1.660	.072	15	1.22	61
WT-20	1-5/8	1.660	.085	14	1.43	61
WT-30	1-5/8	1.660	.095	13	1.59	61
WT-40	1-5/8	1.660	.111	12	1.84	61
Residential	1-7/8	1.900	.055	17	1.08	61
Residential	1-7/8	1.900	.065	16	1.27	61
WT-15	1-7/8	1.900	.072	15	1.41	61
WT-20	1-7/8	1.900	.090	13	1.74	61
WT-30	1-7/8	1.900	.105	12	2.01	61
WT-40	1-7/8	1.900	.120	11	2.28	61
Residential	2-3/8	2.375	.055	17	1.36	37
Residential	2-3/8	2.375	.065	16	1.60	37
WT-15	2-3/8	2.375	.072	15	1.77	37
WT-20	2-3/8	2.375	.095	13	2.31	37
WT-30	2-3/8	2.375	.115	11	2.78	37
WT-40	2-3/8	2.375	.130	10	3.12	37
WT-20	2-7/8	2.875	.110	12	3.25	30
WT-30	2-7/8	2.875	.125	10	3.66	30
WT-40	2-7/8	2.875	.160	9	4.64	30
WT-30	3-1/2	3.500	.145	9	5.20	19
WT-40	3-1/2	3.500	.160	8	5.71	19
WT-30	4	4.000	.145	9	5.98	19
WT-40	4	4.000	.160	8	6.56	19

WT-ColorCoat dark green and black colors are in compliance with ASTM F 934 "Standard Specification for Standard Colors for Polymer-Coated Chain Link Fence Materials"

Wheatland's 3 mil Polyester TGIC Powder WT-Color Coat meets or exceeds the coating requirements of ASTM F 1043 "Standard Specification for Strength and Protective Coatings on Steel Industrial Chain Link Fence Framework"



Wheatland Tube Company 700 South Dock Street, Sharon, PA 16146
 Phone: 800-343-0124 Fax: 888-246-0457 www.wheatland.com