

SYGEF® standard metric



**SYGEF Standard
Solenoid valve type 166
Function A straight-through valve 2/2
ways**

**Nominal voltage 24V DC
With G 1/4 line connection**



Model:

- Material: PVDF
- With manual override
- Electrical connection: cable plug
- Protection class IP 65

DN [mm]	D1_G [inch]	Function	PN [bar]	FPM Code	
3	¼	A	0.0 - 8.0	199 166 505	
4	¼	A	0.0 - 4.0	199 166 506	
5	¼	A	0.0 - 3.0	199 166 507	



**SYGEF Standard
Solenoid valve type 166
Function A straight-through valve 2/2
ways**

**Nominal voltage 230V 50Hz ±10%
With G 1/4 line connection**



Model:

- Material: PVDF
- With manual override
- Electrical connection: cable plug
- Protection class IP 65

DN [mm]	D1_G [inch]	Function	PN [bar]	FPM Code	
3	¼	A	0.0 - 10.0	199 166 515	
4	¼	A	0.0 - 5.0	199 166 516	
5	¼	A	0.0 - 4.5	199 166 517	



**SYGEF Standard
Solenoid valve type 166
Function E mixing valve 3/2 ways
Nominal voltage 24V DC
With G 1/4 line connection**



Model:

- Material: PVDF
- With manual override
- Electrical connection: cable plug
- Protection class IP 65

DN [mm]	D1_G [inch]	Function	PN [bar]	FPM Code	
4	¼	E	0.0 - 2.0	199 166 656	