

PVC-U metric



Solenoid valve type 165 PVC-U
Standard voltage 230V 50Hz
Function A straight-through valve 2/2 ways
With solvent cement sockets metric

- With manual override
- Electrical connection: cable plug
- Protection class IP 65

DN [mm]	d [mm]	PN [bar]	EPDM Code	FPM Code	
15	20	0.5 - 6.0	199 165 012	199 165 002	
20	25	0.5 - 6.0	199 165 013	199 165 003	
25	32	0.5 - 6.0	199 165 014	199 165 004	
32	40	0.5 - 6.0	199 165 015	199 165 005	
40	50	0.5 - 6.0	199 165 016	199 165 006	
50	63	0.5 - 6.0	199 165 017	199 165 007	



Solenoid valve type 165 PVC-U
Standard voltage 115V 50Hz
Function A straight-through valve 2/2 ways
With solvent cement sockets metric

- With manual override
- Electrical connection: cable plug
- Protection class IP 65

DN [mm]	d [mm]	PN [bar]	EPDM Code	FPM Code	
15	20	0.5 - 6.0	199 165 042	199 165 032	
20	25	0.5 - 6.0	199 165 043	199 165 033	
25	32	0.5 - 6.0	199 165 044	199 165 034	
32	40	0.5 - 6.0	199 165 045	199 165 035	
40	50	0.5 - 6.0	199 165 046	199 165 036	
50	63	0.5 - 6.0	199 165 047	199 165 037	



Solenoid valve type 165 PVC-U
Standard voltage 24V DC
Function A straight-through valve 2/2 ways
With solvent cement sockets metric

- With manual override
- Electrical connection: cable plug
- Protection class IP 65

DN [mm]	d [mm]	PN [bar]	EPDM Code	FPM Code	
15	20	0.5 - 6.0	199 165 022	199 165 072	
20	25	0.5 - 6.0	199 165 023	199 165 073	
25	32	0.5 - 6.0	199 165 024	199 165 074	
32	40	0.5 - 6.0	199 165 025	199 165 075	
40	50	0.5 - 6.0	199 165 026	199 165 076	
50	63	0.5 - 6.0	199 165 027	199 165 077	