

## PVC-U metric



### Solenoid valve type 161 PVC-U Nominal voltage 230V 50Hz ± 10% Function E mixing valve 3/2 ways With solvent cement sockets metric

- With manual override
- Electrical connection: cable plug
- Protection class IP 65

DN [mm]	d [mm]	PN [bar]	EPDM Code	FPM Code
10	16	0.0 - 0.6	199 161 040	199 161 035
10	20	0.0 - 0.6	199 161 041	199 161 036
15	20	0.0 - 0.3	199 161 042	199 161 037
15	25	0.0 - 0.3	199 161 043	199 161 038
20	25	0.0 - 0.2	199 161 044	199 161 039



### Solenoid valve type 161 PVC-U Nominal voltage 24V AC/DC Function E mixing valve 3/2 ways With solvent cement sockets metric

- With manual override
- Electrical connection: cable plug
- Protection class IP 65

DN [mm]	d [mm]	PN [bar]	EPDM Code	FPM Code
10	16	0.0 - 0.6	199 161 430	199 161 425
10	20	0.0 - 0.6	199 161 431	199 161 426
15	20	0.0 - 0.3	199 161 432	199 161 427
15	25	0.0 - 0.3	199 161 433	199 161 428
20	25	0.0 - 0.2	199 161 434	199 161 429



### Solenoid valve type 161 PVC-U Nominal voltage 230V 50Hz ± 10% Function F distribution valve 3/2 ways With solvent cement sockets metric

- With manual override
- Electrical connection: cable plug
- Protection class IP 65

DN [mm]	d [mm]	PN [bar]	EPDM Code	FPM Code
10	16	0 - 1.00	199 161 055	199 161 050
10	20	0 - 1.00	199 161 056	199 161 051
15	20	0 - 0.50	199 161 057	199 161 052
15	25	0 - 0.50	199 161 058	199 161 053
20	25	0 - 0.25	199 161 059	199 161 054