

# PROGEF Standard metric

## Solenoid valves



**PROGEF Standard**  
**Solenoid valve type 166**  
**Function A straight-through valve 2/2**  
**ways**  
**Nominal voltage 24V DC**  
**With G 1/4 line connection**



**Model:**

- Material: PP-H
- With manual override
- Electrical connection: cable plug
- Protection class IP 65

DN [mm]	D1_G [inch]	Function	PN [bar]	EPDM Code	FPM Code
3	1/4	A	0.0 - 8.0	199 166 000	199 166 005
4	1/4	A	0.0 - 4.0	199 166 001	199 166 006
5	1/4	A	0.0 - 3.0	199 166 002	199 166 007



**PROGEF Standard**  
**Solenoid valve type 166**  
**Function A straight-through valve 2/2**  
**ways**  
**Nominal voltage 230V 50Hz ±10%**  
**With G 1/4 line connection**



**Model:**

- Material: PP-H
- With manual override
- Electrical connection: cable plug
- Protection class IP 65

DN [mm]	D1_G [inch]	Function	PN [bar]	EPDM Code	FPM Code
3	1/4	A	0.0 - 10.0	199 166 010	199 166 015
4	1/4	A	0.0 - 5.0	199 166 011	199 166 016
5	1/4	A	0.0 - 4.5	199 166 012	199 166 017



**PROGEF Standard**  
**Solenoid valve type 166**  
**Function E mixing valve 3/2 ways**  
**Nominal voltage 24V DC**  
**With G 1/4 line connection**



**Model:**

- Material: PP-H
- With manual override
- Electrical connection: cable plug
- Protection class IP 65

DN [mm]	D1_G [inch]	Function	PN [bar]	EPDM Code	FPM Code
3	1/4	E	0.0 - 4.0	199 166 150	199 166 155
4	1/4	E	0.0 - 2.0	199 166 151	199 166 156