

## WP-209

Active Wall Plate - Computer Graphics Video Line Driver with Composite, Stereo & RJ-45 Pass-Through



The **WP-209** is a wall plate for computer graphics video, composite video, stereo audio and network signals. It provides controls to compensate for signal losses inherent in long cable runs.

### FEATURES

- HDTV Compatible.
- Computer Graphics Resolution - Up to UXGA.
- Front Panel Connections - 1 15-pin HD (F) looping input, 1 3.5mm (F) mini jack, 3 RCA (F) and 1 RJ-45 pass-through.
- Rear Panel Connections - 1 15-pin HD (F) output mounted to a short and extremely flexible cable, 1 balanced stereo audio on a 5-pin terminal block, 3 RCA (F) and 1 RJ-45 pass through.
- Level (Gain) & EQ (Peaking) Control.
- Audio Level Controls - Left & right.
- Dimensions - 11.4cm x 3.3cm x 11.4cm (4.49" x 1.3" x 4.49") W, D, H (US); 15.2cm x 3.3cm x 8.6cm (5.98" x 1.3" x 3.39") W, D, H (EU).
- Wall Plate Size - 2 gang EU/US.

## WP-210

Active Wall Plate - Computer Graphics Video to 5 BNC Line Amplifier



The **WP-210** is a wall plate line driver for computer graphics video signals with resolutions up to and exceeding UXGA. It provides controls to compensate for signal losses inherent in long cable runs.

### FEATURES

- HDTV Compatible.
- High Bandwidth - 400kHz (-3dB).
- Advanced Sync Processing - Ensures compatibility with a wide range of computers.
- Front Panel Connection - 15-pin HD (F) input.
- Rear Panel Connections - 5 BNC (F) output.
- Looping Input.
- Input Signal Termination.
- Selectable Sync Input Impedance - 75Ω (analog) or 510Ω (TTL).
- ID Bit Control.
- EQ (Peaking) Control.
- Dimensions - 6.9cm x 5.0cm x 11.4cm (2.72" x 1.97" x 4.49") W, D, H.
- Wall Plate Sizes - 2 gang EU, 1 gang US.