









The 101L is a high-performance line amplifier for composite video signals. It provides controls to compensate for signal loss inherent in long cable runs.

FEATURES

- Bandwidth 500MHz (-3dB).
- Level (Gain) & EQ (Peaking) Controls Recessed trimmers to prevent unintentional resetting.
- Compact MultiTOOLS® 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-1 universal rack adapter.

TECHNICAL SPECIFICATIONS

INPUT: 1 composite video on a BNC connector, $1Vpp/75\Omega$. OUTPUT: 1 composite video on a BNC connector, $1Vpp/75\Omega$. MAX. OUTPUT LEVEL: 2.5Vpp. BANDWIDTH: 500MHz. DIFF. GAIN: 0.03%. DIFF. PHASE: O.O3Deg. S/N RATIO: 75dB. CONTROLS: Level: -0.8dB to 6.5dB; EQ.: OdB to 8dB. COUPLING: DC. POWER SOURCE: 12V DC, 60mA.

DIMENSIONS: 5.32cm x 4.36cm x 7.25cm (2.09" x 1.72" x 2.85") W, D, H. WEIGHT: 0.15kg (0.33lbs) approx. ACCESSORIES: Power supply.

ACCESSORIES: Power supply.

OPTIONS: RK-1 19" rack adapter.

KRAMER ELECTRONICS, Ltd DIRECTORY OF PRODUCTS 2011/2012 WWW.KRAMERELECTRONICS.COM

