




The SOON is a high-performance power amplifier for balanced or unbalanced stereo audio signals. Either input can deliver a speaker output of 8.4 watts RMS power per channel into a 4Ω load.

FEATURES

- Inputs 1 unbalanced (2 RCA), 1 balanced (terminal block).
- Output 4-pin terminal block (speakers).
- S/N Ratio 55dB.
- Controls Volume knob, On LED.
- Compact Kramer TOOLS™ 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.





TECHNICAL SPECIFICATIONS	

INPUTS:	1 unbalanced stereo audio on RCA connectors; 1 balanced stereo audio on a 5-pin terminal block connector.
OUTPUTS:	1 stereo loudspeaker output on a 4-pin terminal block connector.
OUTPUT POWER:	8.4W RMS per channel into a 4Ω load.
OUTPUT MUSIC POWER:	35W RMS per channel into a 4Ω load.
BANDWIDTH (-3dB):	24kHz.
S/N RATIO:	55dB.
CONTROLS:	<-40dB to +19dB until the compression threshold.
COUPLING:	Input: AC; speakers out: DC.
AUDIO THD + NOISE:	0.5% @1kHz.
AUDIO 2nd HARMONIC:	0.04% @1kHz.
POWER SOURCE:	12V DC, 2.1A.
DIMENSIONS:	12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98") W, D, H.
WEIGHT:	0.3kg (0.66lbs) approx.
ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-3T 19" rack adapter.



6.12 KRAMER ELECTRONICS, Ltd DIRECTORY OF PRODUCTS 2011/2012 WWW.KRAMERELECTRONICS.COM

SPECIALTY AV PRODUCTS) AUDIO PRODUCTS) POWER AMPLIFIERS