


VS-66FW


6-Port FireWire® Matrix Switcher



The **VS-66FW** is a high-performance bidirectional matrix switcher/hub for FireWire® (IEEE 1394 & 1394A) signals. It connects multiple ports to create standard branch/leaf groups.

FEATURES

- **Control** - Front panel, RS-232 (K-Router™ Windows®-based software is included), RS-485, contact closure, & IR remote (included).
- **Transfer Rates** - 100, 200, and 400Mbps.
- **Take Button** - Executes multiple switches all at once.
- **Memory Locations** - Stores multiple switches as presets to be recalled and executed when needed.
- **Front Panel Control Lockout.**
- **Worldwide Power Supply** - 100-240V AC.
- **Standard 19" Rack Mount Size** - 1U.



TECHNICAL SPECIFICATIONS

INPUT/OUTPUT:	6 ports on 6-pin 1394A connectors.
STANDARDS:	Compliant with IEEE 1394-1995 and 1394A-2000 standards.
BUS TRANSFER RATE:	Up to 400Mbps signaling rates for high-performance serial bus.
SOURCED POWER:	12V 1.5A total for any one or all ports.
COMPATIBILITY:	PC and MAC.
CONTROL:	18 front panel pushbuttons and Kramer IR remote receiver on front. RS-232 In/Out on 9-pin D-sub F/M and RS-485 on detachable terminal block.
POWER SOURCE:	100-240V AC, 50-60Hz, 30VA.
DIMENSIONS:	19" x 7" x 1U W, D, H, rack mountable.
WEIGHT:	2.2kg (4.9lbs) approx.
ACCESSORIES:	Power cord, null-modem adapter, Windows®-based control software.

