## 105A

## 1:5 Stereo Audio Distribution Amplifier






The 105A is a high-performance distribution amplifier for unbalanced stereo audio signals. It takes one stereo input and distributes the signal to five identical stereo outputs.

## **FEATURES**

- Level (Gain) Controls.
- S/N Ratio 80dB (unweighted).
- Compact Kramer TOOLSTM 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.







## TECHNICAL SPECIFICATIONS

INPUT: 1 unbalanced stereo/balanced mono, 1Vpp/33kΩ on a 3.5mm mini jack.

OUTPUTS: 5 unbalanced stereo/balanced mono,  $1Vpp/50\Omega$ 

on 3.5mm mini jacks.

MAX. OUTPUT: 5Vpp (> +4dBu).

AUDIO BANDWIDTH (-3dB): 20kHz.

S/N RATIO: 80dB unweighted.

CONTROL: Left and right gain rear trimmers (O to +3.5dB).

COUPLING: AC.

THD: 0.03% (2nd harmonic).

POWER SOURCE: 12V DC, 100mA.

DIMENSIONS: 12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98") W, D, H.

WEIGHT: 0.28kg (0.62lbs) approx.
ACCESSORIES: Power supply, mounting bracket.
OPTIONS: RK-3T 19" rack adapter.

