

VM-1110xi


1:10 Balanced Mono Audio Distribution Amplifier



The VM-1110xi is a high-performance distribution amplifier for balanced mono audio signals on XLR connectors. It can also be configured as a 1:5 distribution amplifier for stereo balanced audio signals.

FEATURES

- Level (Gain) Controls.
- Dual Mode - Configure as 1:10 (mono) or 1:5 (stereo) DA.
- S/N Ratio - 89.3dB.
- Standard 19" Rack Mount Size - 1U.



TECHNICAL SPECIFICATIONS

INPUTS:	2 balanced stereo audio +4dBu/50kΩ on XLR (F) connectors.
OUTPUTS:	10 balanced stereo audio +4dBu/50Ω on XLR (M) connectors.
MAX. OUTPUT LEVEL:	23.8Vpp.
BANDWIDTH (-3dB):	>100kHz.
S/N RATIO:	89.3dB.
CROSSTALK:	-78dB.
CONTROLS:	Level (x2): -0.7dB to +5.1dB, mode selector switches.
COUPLING:	AC (input); DC (output).
AUDIO THD + NOISE:	0.081%.
AUDIO 2nd HARMONIC:	0.006%.
POWER SOURCE:	230V AC, (115V AC USA), 6VA.
DIMENSIONS:	19" x 7" x 1U W, D, H, rack mountable.
WEIGHT:	2.6kg (5.7lbs) approx.
ACCESSORIES:	Power cord.

