


The 903 is a high-performance integrated personal stereo amplifier for

FEATURES

- S/N Ratio 68dB (unweighted).
- Highly Efficient Class D operation.
- Input 3 unbalanced stereo audio on RCA connectors and a single 3.5mm mini pluq.
- Output 6.5mm phone jack and terminal block for speakers.
- Control Volume, bass, mid, treble, balance, and loudness.
- Compact MegaTOOLS® 2 units can be rack mounted side-by-side in a 1U rack space with the optional RK-T2B rack adapter.





TECHNICAL SPECIFICATIONS

INPUTS: 1 unbalanced stereo audio $1Vpp/50k\Omega$ on a 3.5mm mini

jack; 3 unbalanced stereo audio 1Vpp/50k Ω on RCA

connectors.

OUTPUTS: Stereo headphone on a 6.5mm connector; loudspeakers

on a terminal block connector; automatic switching

when a headphone is plugged in.

OUTPUT POWER: $2x10W (4\Omega)$. OUTPUT MUSIC POWER: $2x40W (4\Omega)$. BANDWIDTH (-3dB): 20kHz. S/N RATIO: 77dB @ 1kHz.

CROSSTALK: -73dB @1kHz, all hostile.

CONTROLS: Input selector switches: bass (70Hz), mid (1kHz),

treble (15kHz): +/-13dB; volume, balance and loudness

controls.

COUPLING: AC.
AUDIO THD + NOISE: 0.5%.
AUDIO 2nd HARMONIC: 0.3%.

POWER SOURCE: 12V DC, up to 2.5A.

DIMENSIONS: 19cm x 13.5cm x 2.5cm (7.5" x 5.3" x 0.98") W, D, H.

WEIGHT: O.6kg (1.32lbs) approx.

ACCESSORIES: Power supply.

OPTIONS: RK-T2B 19" rack adapter.

