

## WP-110

### Active Wall Plate - Computer Graphics Video Transmitter



The **WP-110** is a wall plate twisted pair transmitter for computer graphics video signals with resolutions up to and exceeding UXGA. It converts a computer graphics video signal into a twisted pair signal that the TP-120 twisted pair receiver (or other compatible Kramer receiver) converts back into a computer graphic signal.

#### FEATURES

- HDTV Compatible.
- Max. Resolution - WUXGA & 1080p.
- Power Connect™ System - A single connection to the transmitter or the receiver powers both units when the devices are within 150ft (50m) of each other. All the system units must have the Power Connect system to use this feature.
- Advanced Sync Processing - Ensures compatibility with a wide range of computers.
- Front Panel Connection - 15-pin HD (F) input.
- Rear Panel Connection - RJ-45 output.
- Sync Polarity Settings - H & V switches for improved display compatibility with the CAT 5 outputs.
- System Range - Up to 100m (320ft).
- Cable - UTP (unshielded twisted pair) or STP (shielded twisted pair) such as CAT 5.
- Dimensions - 6.9cm x 3.8cm x 11.4cm (2.72" x 1.5" x 4.5") W, D, H (US); 8.6cm x 3.8cm x 8.6cm (3.39" x 1.5" x 3.39") or 8cm x 3.8cm x 8cm (3.15" x 1.5" x 3.15") W, D, H (EU).
- Wall Plate Size - 1 gang EU/US.

## WP-120

### Active Wall Plate - Computer Graphics Video Receiver



The **WP-120** is a wall plate twisted pair receiver for computer graphics video signals with resolutions up to UXGA. It receives a twisted pair signal from the PT-110 transmitter (or other compatible Kramer transmitter) and converts it into a computer graphics video signal.

#### FEATURES

- HDTV Compatible.
- Resolution - WUXGA & 1080p.
- Twisted Pair Input - RJ-45 connector.
- Level (Gain) and EQ (Peaking) Controls.
- Sync Polarity Settings - H & V switches for improved monitor compatibility with the CAT 5 outputs.
- System Range - Up to 100m (320ft), greater distances possible depending on resolution and cable.
- Cable - UTP (unshielded twisted pair) or STP (shielded twisted pair) such as CAT 5.
- Power Connect™ System - A single connection to the transmitter or the receiver powers both units when the devices are within 150ft (50m) of each other.
- Dimensions - 6.9cm x 3.8cm x 11.4cm (2.72" x 1.5" x 4.5") W, D, H (US); 8.6cm x 3.8cm x 8.6cm (3.39" x 1.5" x 3.39") or 8cm x 3.8cm x 8cm (3.15" x 1.5" x 3.15") W, D, H (EU).
- Wall Plate Size - 1 gang EU/US.