

VP-88K 8x8 RGBHV & Balanced Stereo Audio Matrix Switcher



The **VP-88K** is a high-performance matrix switcher for RGBHV video and balanced stereo audio signals. The unit can route any or all inputs to any or all outputs simultaneously.

FEATURES

- High Bandwidth - 350MHz (-3dB) fully loaded.
- HDTV Compatible.
- Kr-isp® Advanced Sync Processing - Ensures compatibility with a wide range of computers (even if the sync level is too low) by restoring the sync signal waveform. Kr-isp® advanced sync processing can be enabled or disabled.
- Vertical Interval Switching.
- Audio Gain Level Controls - Independent gain control of each input and output channel, to match various source levels.
- Audio Breakaway Switching.
- Take Button - Executes a queue of multiple switches all at once.
- Memory Locations - Stores multiple switches as presets (salvos) to be recalled and executed when needed.
- Flexible Control Options - Front panel, RS-232 (K-Router™ Windows®-based software is included), RS-485, Ethernet, IR remote control (included), external IR remote receiver (optional).
- Worldwide Power Supply - 100-240V AC.
- Standard 19" Rack Mount Size - 3U. Rack "ears" included.

VP-885 8x8 Multifformat Video & Balanced Audio Matrix Switcher



The **VP-885** is a high-performance universal matrix switcher for composite video, s-Video (Y/C), component video (Y, Pb, and Pr), balanced stereo audio and S/PDIF digital audio signals. It can route any or all inputs to any or all outputs simultaneously.

FEATURES

- High Bandwidth - 350MHz (-3dB) fully loaded.
- HDTV Compatible.
- Front Panel Control Lockout.
- Take Button - Executes a queue of multiple switches all at once.
- Memory Locations - Stores multiple switches as presets (salvos) to be recalled and executed when needed.
- Analog Audio Breakaway Switching.
- Audio Level Controls - Independent gain control of each input and output channel, to match various source levels.
- Vertical Interval Switching.
- Flexible Control Options - Front panel, RS-232 (K-Router™ Windows®-based software is included), RS-485, Ethernet, IR remote control (included), external IR remote receiver (optional).
- Worldwide Power Supply - 100-240V AC.
- Standard 19" Rack Mount Size - 3U. Rack "ears" included.

