
Mole-Richardson Co.

1,000 WATT MOLORAMA® QUARTZ CYC-STRIPS MULTI-CIRCUIT

USING 1,000, 750 or 500 WATT GLOBES




TYPE 2771 ONE-LIGHT




TYPE 2661 TWO-LIGHT
(1 circuit or 2-circuit)



TYPE 3331 THREE-LIGHT
(1 circuit or 3-circuit)



TYPE 3341 FOUR-LIGHT
(1 circuit, 2-circuit or 4-circuit)




TYPE 3361 SIX-LIGHT
(2-circuit or 3-circuit)



TYPE 2691 EIGHT-LIGHT
(2 circuit or 4-circuit)



TYPE 3391 NINE-LIGHT
(3-circuit)



TYPE 2651 TEN-LIGHT
(2-circuit)



TYPE 3121 TWELVE-LIGHT
(2-circuit, 3-circuit or 4-circuit)

FEATURES

The Molequartz® line of Cyc-Strips are designed to provide a smooth, even field of light on the Cyclorama when the fixtures are hung overhead, mounted on the floor, or both, depending on the requirements and applications. Whatever size or shape your Cyclorama is, there is a wide range of Cyc-strips to choose from. Nine different lengths and from one to four-circuits. Changes in color are made by switching from one-circuit to another. Flow-thru air-cooling are designed into the Cyc-Strip fixtures. The Color Frame Holder is built to allow air to pass between color frame and globe. Quartz Tungsten-Halogen globes from 500 to 1,500 watts are available to give you the intensity you require. Fixtures with 1,500 watt globe sockets are available. Please see the specifications table for more information.

937 North Sycamore Avenue, Hollywood, California 90038 U.S.A.
Tel. (323) 851-0111 • Fax. (323) 851-5593 • E-Mail: info@mole.com • Web: http://www.mole.com
© 2008 Mole-Richardson Co., Hollywood, CA

Mole-Richardson Co.

SPECIFICATIONS

FIXTURE	CIRCUITS	Max. per circuit Amps	Max. per circuit Watts	RATING 120/240 volts Amps Max.	RATING 120/240 volts Watts Max.	LENGTH INCHES	WEIGHT POUNDS
2731 One-Light	1	12.5	1,500	12.5	1,500	11	3
2771 One-Light	1	8.3	1,000	8.3	1,000	11	3
† 2771 One-Light	1	8.3	1,000	8.3	1,000	11	3 1/2
2661 Two-Light	1	16.7	2,000	16.7	2,000	21 1/2	5 1/4
2661 Two-Light	2	8.3	1,000	16.7	2,000	21 1/2	5 1/4
2721 Two-Light	1	25.0	3,000	25.0	3,000	21 1/2	5 1/4
2721 Two-Light	2	12.5	1,500	25.0	3,000	21 1/2	5 1/4
2781 Three-Light	3	12.5	1,500	37.5	4,500	32	7 1/2
3331 Three-Light	1	25.0	3,000	25.0	3,000	32	7 1/4
3331 Three-Light	3	8.3	1,000	25.0	3,000	32	7 1/2
2741 Four-Light	2	25.0	3,000	50.0	6,000	42 1/2	8 3/4
3341 Four-Light	1	33.3	4,000	33.3	4,000	42 1/2	8 1/2
3341 Four-Light	2	16.7	2,000	33.3	4,000	42 1/2	8 3/4
3341 Four-Light	4	8.3	1,000	33.3	4,000	42 1/2	9
2761 Six-Light	2	37.5	4,500	75.0	9,000	63 1/2	13 1/4
2761 Six-Light	3	25.0	3,000	75.0	9,000	63 1/2	13 1/4
3361 Six-Light	2	25.0	3,000	50.0	6,000	63 1/2	13 1/4
3361 Six-Light	3	16.7	2,000	50.0	6,000	63 1/2	13 1/4
2691 Eight-Light	2	33.3	4,000	66.6	8,000	84 1/2	16
2691 Eight-Light	4	16.7	2,000	66.6	8,000	84 1/2	16
3391 Nine-Light	3	25.0	3,000	75.0	9,000	95	19 1/2
2651 Ten-Light	2	41.7	5,000	83.3	10,000	105 1/2	20 3/4
3121 Twelve-Light	2	50.0	6,000	100.0	12,000	126 1/2	26
3121 Twelve-Light	3	33.3	4,000	100.0	12,000	126 1/2	26
3121 Twelve-Light	4	25.0	3,000	100.0	12,000	126 1/2	26

† Leads both ends with twist-locks for interconnecting up to 4 One-Light unit

SOCKETS: Compressible single contact. (two per globe).
SWITCH: None.
CONNECTIONS: Three extra-flexible 36" K-Fiber leads per circuit. (when ordering, specify type of plugs required and number of circuits). Three wire plugs with ground circuit are standard.
CONSTRUCTION: Solid and perforated sheet steel with aluminum end casting.
REFLECTOR: Aluminum, special Molebrite® Alzak surface.
SIZE: 6 1/4" x 4 1/2" deep. With Direct Mounting Color Frame Holder; 13 1/8" high x 12 3/4" deep.
FINISH: Bake maroon enamel.
WEIGHTS:
FIXTURE: See chart.
COLOR FRAME HOLDER:
One-Unit—3 pounds each.
Two-Unit—5 1/2 pounds each.
Three-Unit—7 1/2 pounds each.
FILTER FRAME: 13 ounces each.

GLOBE TABLE

Base, recessed single contact. Burn horizontal ±4° T-3 bulb; 4 11/16" M.O.L.

Watts	Ordering Code	Color Temp.°K	Finish	Volts	Life Hours	Amps
1000	FCM	3200	Clear	120	400	8.3
1000	FHM	3200	Frost	120	300	8.3
800	EME	3200	Clear	240	250	3.3
800	EMF	3200	Frost	240	250	3.3
750	EJG	3200	Clear	120	400	6.3
750	EMD	3200	Frost	120	400	6.3
500	FDF	3200	Clear	120	400	4.2
500	FDN	3200	Frost	120	400	4.2
500	FCL	3000	Clear	120	2000	4.2
300	EHM	2950	Clear	120	2000	2.5
300	EHZ	2950	Frost	120	2000	2.5

Globes not included in price of lamp.
See price list for complete details.

ACCESSORIES

26120 C-Clamp & Hanger
26530 Floor Mounting Brackets (Pair)
26540 Double Hangers & C-Clamps (Pair)
26546 Safety Cable
27220 Direct Mounting Color Frame Holder (Two-Unit)
Used on Two-Light (1 Req'd.), Four- Light (2 Req'd.), Six-Light (3 Req'd.), Eight-Light (4 Req'd.), Ten-Light (5 Req'd.), and Twelve-Light (6 Req'd.).
27253 One-Unit Hanger & C-Clamp
Supports one Two-Light unit.
27240 Molequik Filter Frame
Direct Mounting Color Frame Holder needed for mounting. One per globe when needed.
27320 Direct Mounting Color Frame Holder (One Unit)
‡Used on One-Light units.
27726 One-Unit Hanger & C-Clamp
33310 One-Unit Hanger & C-Clamp
Supports one Three-Light unit.
33920 Direct Mounting Color Frame Holder (Three-Unit)
Used on Three-Light (1 Req'd.), Six-Light (2 Req'd.), Nine-Light (3 Req'd.), and Twelve-Light (4 Req'd.).



Type 26546
SAFETY CABLE
(Recommended installation on fixture at factory)
Used on hanging units where extra safety measures are required.

937 North Sycamore Avenue, Hollywood, California 90038 U.S.A.
Tel. (323) 851-0111 • Fax. (323) 851-5593 • E-Mail: info@mole.com • Web: http://www.mole.com
© 2008 Mole-Richardson Co., Hollywood, CA