



# Side Compression Shear

## Processes:

Steel Mill Scrap

Pipe and Plate

No. 1 Heavy Melting Scrap

No. 2 Heavy Melting Scrap

Selected sections of freight cars  
and ship scrap.

Harris has gone back to the drawing board and reinvented a better shear that provides higher performance and reduced energy usage, utilizing Harris' patent-pending EHD (Efficient Hydro-Dynamic) hydraulic system design, all while reducing your maintenance downtime - keeping your operation running smoothly.



# Side Compression Shear

## STANDARD FEATURES

### PERFORMANCE

- High Pressure 345 bar System
- High Flows Up to 6050 lpm
- 4-8 cuts per minute (dry cycle)

### POWER UNIT

- Each Pump / Motor Group produces 1200 lpm @ 2300 RPM (40 bar)
- Power Unit Options:
  - 4 motor (375 kW) 4845 lpm
  - 5 motor (465 kW) 6050 lpm
- Patent Pending EHD Motor-Pump Drive
- Dual Filtration / Cooler Circuit – with online particle monitoring.
- Compact Design – ships as fully tested, single unit.

### EFFICIENT HYDRO-DYNAMICS (EHD)

- Facilitates higher flows by varying motor and pump speed up to 2300 rpm:
  - 30% Higher Flow - Domestic
  - 59% Higher Flow – International
- Reduce energy demand by up to 50 percent.
- Allows cylinder Acceleration/ Deceleration Control: Energy Efficient – motors set to idle when not in use (more efficient than soft start).

### MACHINE PIPING

- Large diameter, heavy-walled, mechanical pipe rated for high flows at high pressure.
- Bolted pipe connections
- Weld free – no scale
- Alloy steel pipe
- CNC bending

### SHEAR FRAME

- Same knives and knife seats are used in both the Crosshead and Fixed locations.
- Very robust interlocking plate design for enhanced rigidity, strength, ease of maintenance and operation.
- Welded interlocking plate-to-plate joints for improved load resistance.
- Innovative Crosshead / Chute interface to guide movement of sheared scrap.
- Chute is mechanically driven by motion of Crosshead.
- Limits vertical free fall of sheared scrap to reduce wear rates to exposed surfaces.
- Controls flow of sheared scrap to minimize spillage.
- Harris (BSH) style knife adjustment mechanisms.

### CROSSHEAD AND CLAMP

- Double trapezoidal design provides improved distribution of loads throughout shear frame.
- Crosshead bends material prior to shearing in order to reduce required shear load.
- Composite self-lubricating bearing pads guide Crosshead and Clamp throughout range of motion.
- Wear Liner plates in Crosshead and Clamp throat are replaceable without removing Crosshead or Clamp from shear.
- Clamp is designed to reduce jamming by limiting scrap migration into the guides.

**Call today for more information**

770-631-7290

800-373-9131

[www.harrisequip.com](http://www.harrisequip.com)

\*All products and features are subject to change. Photos not necessarily representative of new equipment



Harris © 2010 - SCShear10 -