

125 & 750 GPM

Model	Height (in/mm)	Width (in/mm)	Weight (lbs/kg)	Inlet (in/mm)	Outlet (in/mm)	GPM (GPM/LPM)	Volts
FP12300-12	22 (559)	13 (330)	45 (20)	2 1/2 (64) flange	2 1/2 (64)	750 (2839)	12
FP12300-24	22 (559)	13 (330)	45 (20)	2 1/2 (64) flange	2 1/2 (64)	750 (2839)	24
FP1-125-RCE	7 1/2 (191)	10 1/4 (260)	18 (8)	1 1/2 (38) flange	1 1/2 (38)	350 (1325)	12
FP1-125-RCE-24	7 1/2 (191)	10 1/4 (260)	18 (8)	1 1/2 (38) flange	1 1/2 (38)	350 (1325)	24
FP3-750-HYD	22 (559)	13 (330)	52 (8)	3 (76) 150# RF flange	2 1/2 (64)	750 (2839)	

Electric Nozzles

For use with electronically-controlled monitors. Available in 12 and 24 VDC. Material: alloy.



FP10818E

- 1-1/2" (38mm) inlet
- Selectable gallonage - 200, 250, 350 GPM
(757, 949, 1325 LPM)



FP10817E

- 2-1/2" (64mm) inlet
- Selectable gallonage - 250, 400, 550, 750 GPM
(949, 1514, 2082, 2839 LPM)
- 24VDC only

125 & 750 GPM

Model	Weight (lbs/kg)	Inlet (in/mm)	Teeth	GPM (GPM/LPM)
FP10818E -12 or 24	7 (3)	1 1/2 (38)	Spinning	200-350 (757-1325)
FP10817E -24	8 1/2 (4)	2 1/2 (64)	Fixed	250-750 (949-2839)