



Part Number: 43003

Description: Firomatic® Fusible Valve

Packaging: Poly bagged & tagged

Includes:

1 - Firomatic® Fusible Valve Designed to automatically close when acted upon by heat of 165° F, manufactured primarily for oil burner installations. This valve has been designed with the fusible element in the handwheel, simply replace the low cost handwheel to reset and restore the valve, eliminating the need to replace the valve. These valves can be operated manually and are provided with self-adjusting stuffing box and back seat features, which prevents leaks at the valve stem.



3/8" (F) NPT

1/4" (m) NPT

Part Number:

43005 - 24" L x 1/2" Flexible Hose

43006 - 36" L x 1/2" Flexible Hose

Description: Flexible Steel Zinc Plated Braided Hose

Packaging: Poly bagged & tagged

Includes:

1 - Flexible hose from above list with 1 adaptor fittings
 These hoses have a 1/4" NPT fittings on both ends, for expediting the installation of the Tigerloop® or Flow Control® de-aerator. Made from Perbunan rubber (inside), which is impervious to oil, water and air. This product has a diversity of uses.

Extra adaptors are available, our P/N: 43009

Specifications

Pressure rating: 143 psi
 Max. Operating Temp: 165° F
 Max. Flow Rate: 20 GPH
 Suction: 6 Bar



NOTE: Fits or replaces Buderus #108902

Part Number:

43019 - 24" L x 1/2" Flexible Hose

43020 - 36" L x 1/2" Flexible Hose

Description: Flexible Steel Zinc Plated Braided Hose

Packaging: Poly bagged & tagged

Includes:

1 - Flexible hose from above list

We are proud to introduce our new 36" long galvanized blue braided hose.

This hose features:

(2) 3/8" female flare swivel ends to accommodate swinging door burner installations and hose replacement.

-No more hose twisting!

-Inside flare ensures a snug fit.

-Swivel ends make installation simple.

-Tested by the manufacturer to meet industry standards.



Part Number:

43021 - 36" L x 1/2" Bio-fuel flexible hose

Description: Flexible Steel Zinc Plated Braided Hose

Packaging: Poly bagged & tagged

Includes:

1 - Flexible hose from above list with 1 adaptor fittings

These hoses have a 1/4" NPT fittings on both ends, for expediting the installation of the Tigerloop® or Flow Control® de-aerator. This oil- and fuel-resistant flexible elastomer hose is fitted with galvanized steel wire braiding as a pressure or strength bearer. The polymer basis of the inner core is HNBR (hydrogenated butadiene acrylnitrile rubber) which is highly resistant to high temperature. Suitable for use with biodiesel. This product has a B100 Bio-fuel rating. Look for the "Green Colored" braid.

Extra adaptors are available, our P/N: 43009

Specifications

Pressure rating: 143 psi
 Max. Operating Temp: 165° F
 Max. Flow Rate: 20 GPH
 Suction: 6 Bar



NOTE: Fits or replaces Buderus #108902