

ALL PRODUCTS CATALOG

Apollo® AR™ Ball Valves

APOLLO AR™ BALL VALVE RATINGS

Apollo AR actuator ready ball valves feature an ISO 5211-style mounting pad with no handle to throw away. They are made for high cycle applications, and like all Apollo valves, the bodies are cast to the highest metallurgical standards for long service life.

They are available in stainless steel, carbon steel and bronze. They feature a live loaded multi-stacked "V"-ring stem packing. All models come standard with a stainless steel ball and stem, and multifill seats, seals and packing rated up to 2000 psig or to 450°F, or to 250 psig saturated steam. (Bronze rated to 600 psig.)

76-AR SERIES



Stainless steel standard port ball valve. Investment cast components; ISO mounting pad and advanced live loaded packing design. Latch lock handle available. Sizes 1/4" to 3".

71-AR SERIES



Bronze standard port ball valve with threaded ends, ISO mounting pad, and advanced live loaded packing design. Latch lock handle available. Sizes 3/4" to 3".

77-AR SERIES



Bronze full port ball valve with threaded ends. ISO mounting pad and advanced live loaded packing design. Latch lock handle available. Sizes 1/4" to 2".

77D SERIES



Full port bronze ball valve with an integral ISO 5211 mounting pad. Double o-ring stem seal and MPTFE seats and bearings. Sizes 1/2" to 2" with standard stainless steel ball and stem.

89-AR SERIES



Carbon steel standard port ball valve. Investment cast components, ISO mounting pad and advanced live loaded packing design. Latch lock handle available. Sizes 1/4" to 3".

Heavy Duty Apollo Ball Valves

- Blow-out proof stem
- Field repairable
- RPTFE seats and stuffing box rings
- Meets WW-V-35C federal standards
- Fire safe designs available
- Expanded pressure ranges
- High performance alloys

72 SERIES



Carbon steel high pressure ball valve. Rated 3000 psig. Sizes 1/4" to 2". Pressure is body rating.

87A SERIES



Stainless steel Class 150 and 300 flanged valve. Regular or full port, ISO 5211 actuator mounting pad. Sizes 1/2" to 12"