

ALL PRODUCTS CATALOG

Air and Gas Cocks

41 SERIES – MODEL AC



Brass air cocks with "tee" handle or lever handle. Spring and nut bottom with a wide range of connections available.

54 SERIES – MODEL GCA



Gas hose-end shut-off valves. 1/8" NPT or standard tube sizes. Capacity: 56,500 Btu/hour. Pipe sizes: 3/8" to 3/4".

56 SERIES – MODEL GCP



Pilot gas cocks. 1/2 psig for 32°F to 125°F service. CSA design certified. 1/8" MNPT x various 1/4" tube connections.

GB-15, GB-16 SERIES – MODEL GBVU, GBVA



These Apollo International™ gas appliance ball valves are designed for natural gas, manufactured and mixed gas, liquefied petroleum gasses and LP gas-air mixture applications. They comply with the latest editions of ANSI, CSA, and UL published standards.

GB-10 SERIES – MODEL GBV



CSA design-certified manual shut-off ball valves for many fuel types for up to 5 psig. Capacities: 300,000 to 1.1 million BTu/hour. Standard female x female threaded connection. Sizes: 3/8" to 1".

GB-50 SERIES – MODEL GBVB



UL and CSA design-certified manual gas shut-off ball valves for many fuel types for up to 5 psig. Standard female threaded connections. Available with single or dual tapped gas ports. Sizes: 1/2" to 2".

77G-UL SERIES



77G-UL Series ball valve is a UL and CSA listed fuel shut off valve approved for a variety of flammable gasses and liquids. Bronze body, premium multi-fill MPTFE seats and stem packing. "Solid Ball" design for true full port flow. Sizes 1/2" to 1" NPT.

80 SERIES



Bronze ball valve for LP gas, natural gas, flammable liquids and heated oil. Adjustable packing gland, UL listed. Sizes 1/4" to 3".