

## Control4<sup>®</sup> 4-Zone Amplifier and 8-Zone Amplifier

## Control4<sup>®</sup> 4-Zone Amplifier C4-8AMP1-B Control4<sup>®</sup> 8-Zone Amplifier C4-16AMP3-B

Control4 amplifiers provide high-quality sound to four or eight audio zones from distinct sources. Regardless of the size of your home or project, you'll enjoy a powerful, multi-room music solution that's fully integrated into your Control4 system. Both amplifiers offer full matrix switching, advanced parametric equalizer, independent input gain control and volume limiting capabilities.

- The 4-zone amp lets you enjoy 60W of high-quality sound from 4 analog and 2 digital input sources in 4-speaker output zones.
- The 8-zone amp offers 120W of high quality sound from 8 analog input sources in 8-speaker output zones.
- The 4-zone amp supports Auto Power-Save mode—when it's not in use, it drops into energy-conservation mode using just 2 watts of power.
- Tweak the sound on any speakers using the parametric equalizer. The Control4 Equalizer app lets you view and adjust a range of settings from on-screen and touch-screen devices.





## 

Take full advantage of the built-in parametric equalizer in your Control4 4-zone and 8-zone (V3) amplifiers with the Control4 Equalizer app.

www.4store.com

Control4®	Amplifiers
0011011	/ inpiniers

	Control4® 4-Zone Amplifier	Control4® 8-Zone Amplifier (Multi-Channel Amp)
Model Number	C4-8AMP1-B	С4-16АМРЗ-В
Analog Input Sources	8	16
Digital Input Sources	2	0
Speaker Output Zones	4	8
Line Level Output Zones	0	0
Rated Wattage per Channel	60 @ 8 ohms 120 @ 4 ohms	120 @ 8 ohms 220 @ 4 ohms
Frequency Response	19 Hz - 20 kHz +/5dB @ 8 ohms +/2dB @ 4ohms	19 Hz - 20 kHz +/5dB @ 8 ohms +/2dB @ 4ohms
Signal-to-Noise Ratio	>95 dB	>95 dB
THD	<0.02% - 20 Hz - 20 kHz	<0.05% - 20 Hz - 20 kHz
Network Connectivity	10/100 BaseT Ethernet	10/100 BaseT Ethernet
Tone Controls	Bass, Treble, 5-band parametric EQ	Bass, Treble, 5-band parametric EQ
Display	Backlit Monochrome LCD	Backlit Monochrome LCD
Full Matrix Switching	Yes	Yes
Independent Gain Control per Zone	Yes	Yes
Rack Mount Kit	3U Rack Mount Kit with ventilation (C4-3URMK-B) 3U Rack Mount Kit non-vented (C4-3URMK-NV-B)	4U Rack Mount Kit with ventilation (C4-4URMK-B) 4U Rack Mount Kit non-vented (C4-4URMK-NV-B)
Accessories	Banana Plug Kit (C4-BPLUG8)	Banana Plug Kit (C4-BPLUG8)
Voltage	120 - 240 VAC	120 - 240 VAC
Hertz	50/60 Hz	50/60 Hz
Operational Temperature	32° F - 104° F (0° C - 40° C)	32° F - 104° F (0° C - 40° C)
Humidity	5% - 95% Non-condensing	5% - 95% Non-condensing
Storage Temperature	-4° F - 158° F (-20° C - 70° C)	-4° F - 158° F (-20° C - 70° C)
HxWxD	3.5" x 17" x 18" (89mm x 432mm x 457mm)	5.25" x 17" x 16" (133mm x 432mm x 406mm)
Weight	18 lbs (8.16 kg)	28 lbs ( 12.7 kg)

For product photos, documentation and installation instructions, visit: http://www.control4.com/dealer/products/av/4-zone-amplifier http://www.control4.com/dealer/products/av/8-zone-amplifier

