

# FULLTRAP™

The FullTrap™ is a combination broadband absorber and bass trap that is mounted on a wall surface to control excessive bass in a room. This is achieved by combining three acoustical principles into a single device.

To handle mid-range and upper frequencies, a 3" thick front absorptive panel made from 6 lbs. per cubic foot high-density encapsulated fiberglass is employed. Behind the acoustic panel is a diaphragmatic dense-mass membrane that acts as a low frequency resonator to absorb bass below 75Hz. Behind the membrane is an air cavity that is created by the wood composite enclosure which serves to further attenuate bass in the troublesome 100Hz region.

The FullTrap enclosure is made from MDF wood composite with a black, easy to clean melamine finish and ships flat to reduce freight. Final assembly is performed on site using a simple household screwdriver. Building a FullTrap takes about 15 minutes from start to finish! The Fulltrap is available in a choice of three panel colors: black, beige and gray.

**SPECIFICATIONS:**

<b>FRAME MATERIAL</b>	Black melamine laminated MDF
<b>DIMENSIONS</b>	24" (610mm) x 48" (1219mm) x 8" (203mm)
<b>PANEL MATERIAL</b>	Formed, semirigid inorganic glass fibers; Density 6.0 lbs. pcf. (96 kg/m3)
<b>FABRIC FACING</b>	Acoustically transparent polyester
<b>DIAPHRAGMATIC MEMBRANE</b>	Loaded vinyl, 1 lbs. per square foot
<b>ORDER NUMBER</b>	Z840-1100-xx (xx denotes color code 00=Black; 03= Beige; 08=Grey)
<b>RECYCLED CONTENT</b>	Over 50%


**CORNER MOUNTING ABSORPTION CHARACTERISTICS\*:**


Sound absorption coefficient data

40Hz	63Hz	125Hz	250Hz	500Hz	1kHz	2kHz	4kHz	5kHz
.20	.57	1.76	1.27	1.33	1.23	1.19	1.13	1.13

**WALL MOUNTING ABSORPTION CHARACTERISTICS\*:**

Sound absorption coefficient data

40Hz	63Hz	125Hz	250Hz	500Hz	1kHz	2kHz	4kHz	5kHz
.37	.59	.83	.80	1.00	1.02	.98	.94	.95



Due to the broadband nature of the diaphragmatic limp mass used in both the MaxTrap and FullTrap, the device will naturally vibrate at the room's resonant frequency. This will result in greater effectiveness at the peak frequency, in particular when corner mounted. This is clearly demonstrated in the Corner Placement Test where the resonant frequency in the laboratory is 80Hz. For reference, the standard Sound Absorption Coefficient wall-mount test was also performed. Although limited in scope, it provides typical data down to 100Hz and expected performance at lower frequencies as calculated by the laboratory. It should be noted that bass absorption tests are difficult to produce due to the extremely long wavelengths of lower frequencies and available room size. The tests as described above are as a result of our working with Riverbank Laboratories to deliver the most accurate findings possible given the limitations of the facility and practical mounting methods.

