

PDT Series is an Installer Favorite

Field Configurable Power Strip

All hardwired PDT Series models can be configured as:

- Isolated (technical) or non-isolated ground
- Single or dual circuit



PDT Series Model Details on Facing Page



96-01031 for full

96-01031 for full

PDT-2X1015 - Ground facing J-Box

PDT-2X1015T - Ground facing away from J-Box





PDT-2X1020 - Ground facing J-Box

PDT-2X1020T - Ground facing away from J-Box









•==• Typical 10 outlet

Typical 6 outlet

·B B· · 🕒 🕒 ·



PD Dimensions

Typical 12 outlet ·B B· ·D:D: •••••


used in 15 and 20 Amp single, multiple and isolated ground circuits with 8" tails used in 15 Amp single and dual circuits

Additional Mounting Brackets See Illustrations on Facing Page •

PB-90 bracket orients power outlets on any vertical power strip to the front or back of the enclosure*. Allows mounting of power strips alongside mounted equipment in wider WRK Series racks. Use PB-5A brackets to mount Middle Atlantic Products power strips in AXS, Slim 5, RL, RLA and MK Series racks, or to the rackrail of any rack. To mount power strips in the SR and DWR Series wall racks, use PB-DWR brackets. Cable management clips available for PDT Series power strips, sold in packs of 6.

Part #	Description							
PB-90	brackets mount vertical power to face front or back of any rack* (pair)							
PB-5A	brackets to mount vertical power strips on rear rackrail (pair)							
PB-DWR	brackets to mount vertical power strips in DWR & SR Series wall racks (pair)							
*Requires LBFR-5A-xx to mount inside Slim 5 or AXS Series Racks								








PDT Series


		Part #	Chassis Style	Circuits	# of Outlets	Outlet Type	Chassis Length	Termination	Wire Gauge	Isolated (Technical) Ground	Circuit Arrangement	Fits Racks Coded	Standard Number
o Justintertek	15	PDT-2X1015	PDT	(2) 15 Amp	20	5-15R	72-3/4"	J-Box	12	Field Configurable	1-2-1-2-1-2-1-2-1-2-1-2-1-2-1-2	P	1, 2
	Amp	PDT-2X1015T	PDT	(2) 15 Amp	20	5-15R	72-3/4"	J-Box	12	Field Configurable	1-2-1-2-1-2-1-2-1-2-1-2-1-2	P	1, 2
a	20	PDT-2X1020	PDT	(2) 20 Amp	20	5-20R	72-3/4"	J-Box	12	Field Configurable	1-2-1-2-1-2-1-2-1-2-1-2-1-2-1-2	P	1, 2
o Intertek	Amp	PDT-2X1020T	PDT	(2) 20 Amp	20	5-20R	72-3/4"	J-Box	12	Field Configurable	1-2-1-2-1-2-1-2-1-2-1-2-1-2-1-2	P	1, 2


PD Series

		Part #	Chassis Style	Circuits	# of Outlets	Outlet Type	Chassis Length	Termination	Wire Gauge	Isolated (Technical) Ground	Circuit Arrangement	Fits Racks Coded	Standard Number	
o us Intertek		PD-1215J-S	PD	(1) 15 Amp	12	5-15R	30-1/2"	J-Box	14	No	1-1-1-1-1-1-1-1-1	E	1, 2	
	15 Amp	PD-1215	PD	(1) 15 Amp	12	5-15R	57"	3/8" flex, 36" length	14	No	1-1-1-1-1-1-1-1-1	N	1, 2	
		PD-2X615	PD	(2) 15 Amp	12	5-15R	57"	3/8" flex, 36" length	14	No	1-1-2-2-1-1-2-2	N	1, 2	
c us	20 Amp	PD-620J-IG	PD	(1) 20 Amp	6	5-20R	30-1/2"	J-Box	12	Yes	1-1-1-1-1	E	1, 2	
		PD-1020J-IG	PD	(1) 20 Amp	10	5-20R	44"	J-Box	12	Yes	1-1-1-1-1-1-1-1	J	1, 2	
		PD-2X620J	PD	(2) 20 Amp	12	5-20R	61"	J-Box	12	No	1-1-2-2-1-1-2-2	N	1, 2	
		PD-1220J-IG	PD	(1) 20 Amp	12	5-20R	61"	J-Box	12	Yes	1-1-1-1-1-1-1-1-1	N	1, 2	
		PD-1220J	PD	(1) 20 Amp	12	5-20R	61"	J-Box	12	No	1-1-1-1-1-1-1-1-1	N	1, 2	
	1. Conforms to UL Standard 5							2. Certified to CSA Standard C22.2 No. 62						

Additional Mounting Brackets







m