

Desktop Racks

DTRK Series Desktop Rack

NEW!

UL LISTED EIA/TIA Compliant GREENGUARD Indoor Air Quality Certified

This new compact rack series provides a rackmounting solution for desktop installations and also great for under desk applications. Available options include vented and plexi front doors, and a brush grommet rear access panel for simple and clean cable entry routing. Another option is the LL-DTRK adapter kit, which enables the use of certain 21" vertical LeverLock™ accessories (channels and angles only – not compatible with mounting plates). These are part of the patent-pending LeverLock™ tool free internal management system. For more on the LeverLock system, please see pg. 10. Runner kit option 5-RS20 is also available, see pg. 51.

- Static load capacity - 1,200 lbs.
- UL Listed in US and Canada. UL Listed load capacity - 300 lbs.
- GREENGUARD Indoor Air Quality Certified for Children and Schools (the most strict level)



DTRK-1418



DT-PVFD-14



DT-RAP14



LeverLock™ requires optional LL-DTRK Kit

Part #	Racking Height	Overall Height	Useable Depth	Overall Depth	Overall Width	Vented Front Door	Plexi/Vented Front Door	Solid Rear Access Panel w/ Brush Cable Entry	LL-DTRK Allows Vertical LeverLock™ Height	Commercial Grade Casters
DTRK-718	12-1/4" (7 space)	14-1/8"	18-1/2"	19-1/2"	21-3/8"	DT-VFD-7	DT-PVFD-7	DT-RAP7	–	DTRK-W
DTRK-1018	17-1/2" (10 space)	19-3/8"	18-1/2"	19-1/2"	21-3/8"	DT-VFD-10	DT-PVFD-10	DT-RAP10	21"	DTRK-W
DTRK-1218	21" (12 space)	22-7/8"	18-1/2"	19-1/2"	21-3/8"	DT-VFD-12	DT-PVFD-12	DT-RAP12	21"	DTRK-W
DTRK-1418	24-1/2" (14 space)	26-3/8"	18-1/2"	19-1/2"	21-3/8"	DT-VFD-14	DT-PVFD-14	DT-RAP14	21"	DTRK-W
DTRK-1818	31-1/2" (18 space)	33-3/8"	18-1/2"	19-1/2"	21-3/8"	DT-VFD-18	DT-PVFD-18	DT-RAP18	21"	DTRK-W

•for more info refer to pgs. 96-117

Slim 2 Series Sloped Desktop Racks

The 2-10 rack ships fully assembled and incorporates a sturdy black steel open frame and removable black laminate side panels. Featuring a sloping rack face for easy equipment viewing, this frame can be easily joined, with the open sides and bottom allowing for quick wire passage. Front and rear heavy-gauge, 10-32 threaded rackrail is standard.

- GREENGUARD Indoor Air Quality Certified for Children and Schools (the most strict level)

Part #	Racking Height	Top Depth	Bottom Depth	Overall Height
2-10	17-1/2" (10 space)	14-1/8"	18"	19-3/8"

Ready-To-Assemble Black Laminate - Ships Flat!

SLIM-2M racks assemble quickly and easily with provided hardware. Constructed with 5/8" thick furniture-grade MDF board, these black laminate racks are available in 6 or 10 space sizes and feature a sloping rack face for easy equipment viewing. Front and rear heavy-gauge, 10-32 threaded rackrail is standard.

- GREENGUARD Indoor Air Quality Certified for Children and Schools (the most strict level)

Part #	Racking Height	Top Depth	Bottom Depth	Overall Height
2-6M	10-1/2" (6 space)	15-7/8"	17-7/8"	12-3/4"
2-10M	17-1/2" (10 space)	14-3/4"	17-7/8"	19-5/8"

Spec. # 96-036 for full product info. A&E EIA/TIA Compliant RoHS GREENGUARD Indoor Air Quality Certified

2-10 shown with sides removed



2-10 shown with sides installed



2-10M





ISRK Series Under Desk/Mobile Presentation Rack



ISRK Series sloped rack features scuff resistant Glide-Away™ front door.

For use in all applications where an under desk or mobile presentation rack is required, including control desk, mixing, testing, and recording desks.

Structural Features

- Rolls under all standard height desks
- 15° slope provides an ergonomic viewing angle when used under-desk
- Scuff resistant Glide-Away™ front door easily hides away, and requires minimal clearance in cramped environments
- Features 12 useable rackspaces, front and rear, to ensure all useable space is accessible
- Knockouts on face of rack accept RPS Series remote power switch and low-voltage Decora® style switches or devices
- Secure, locking front door and full height locking rear door, both are easily removable
- Durable, aesthetically pleasing granite gray finish
- Up to 21-3/4" useable depth

Thermal Management

- Designed for effective passive thermal management

Cable Management

- Abundant internal cable lacing points facilitate cable management
- Removable electrical knockout panels for ease of cable entry/exit

Regulatory / Certifications

- Robust 200 lb. weight capacity
- UL Listed in the US and Canada
- GREENGUARD Indoor Air Quality Certified for Children and Schools (the most strict level)

Part #	Description	Overall Height
ISRK-12GY	12 rackspace under desk/mobile presentation rack	26-7/8" (including casters)
WS1-ISRK-21G	ISRK work surface, graphite finish	adds 1-1/8"
MMB1X1*	single LCD mount, articulating, black finish	-
*28 lb. weight capacity		



ISRK-12GY

shown with optional work surface and LCD mount



shown open with Glide-Away™ door stowed in bottom recess

shown with door extended

