



Model #: TLP76MSG

6 individually controlled eco outlets plus 1 always on outlet, 6-ft cord, 1080 joules ECO-SURGE Home/Business Surge Suppressor



Highlights

- Want to save \$30/year on your energy bill? Learn how.
- Individual outlet control
- 1080 joules
- 7 outlet / 6-ft cord
- Diagnostic LEDs
- \$25,000 Ultimate Lifetime Insurance (USA and Canada Only)

Description

Want to save \$30 per year on your energy bill? Learn how. Tripp Lite's TLP76MSG offers reliable, GREEN surge technology that protects your computer and peripherals as well as the environment and your wallet. Energy-saving outlet configuration reduces energy waste (phantom loads) by cutting AC power to unused peripherals. The TLP76MSG has one always on outlet for those peripherals that need constant power like a fax machine, DVR or router. It also offer convenient, individual outlet switches that allow users to select which device is turned on and off. The TLP76MSG has 7 total outlets, 6 foot cord and diagnostic LEDs to warn of wiring problems and suppressor damage. Network-grade AC suppression rated at 1080 joules shields equipment from surges and line noise. Designed with an attractive cool gray suppressor housing, the TLP76MSG can accommodate up to 4 transformer plug outlets offering convenient protection of desktop computer equipment and accessories. \$25,000 connected equipment insurance (USA and Canada Only).

Applications

• Ideal for any desktop, network or home computing application requiring AC protection

Package Includes

- TLP76MSG ECO-SURGE Home/Business Theater Surge Suppressor
- Instruction manual with warranty information

Features

- Energy-saving green outlets allow individual outlet control using illuminated power switches for cutting power to peripherals not in use.
- Six green outlets have their own illuminated ON/OFF switch for cutting power to peripherals when they are not in use. One "Always On" outlet provides continuous power for devices such as DVRs (TiVo), cable and satellite boxes, modems, routers and fax machines.
- In addition to the individual illuminated outlet switches, an illuminated Master Switch controls power to all outlets (except the Always On outlet) at once. It can override other "ON" settings to cut power to all switched outlets at once.
- Protected (Green) LED assures protection is present & Always On (Red) LED indicates that the Always On outlet is receiving power.
- 1080 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans).

•

Specifications

OVERVIEW	
Intended Application	Green (Energy Saving)

Transformer accommodation INPUT Nominal Input Voltage(s) Supported Recommended Electrical Service Input connection type Input cord length (ft.) Supports 1 large 120V AC 120V AC 120V (110-125) 6	ght angle outlets e transformer without covering remaining outlets, accepts up to 4 transformers total V)
Frequency compatibility Outlet quantity / type 7 x NEMA 5-15 Outlet Type Single row of right Transformer accommodation INPUT Nominal Input Voltage(s) Supported Recommended Electrical Service Input connection type Input cord length (ft.) 60 NEMAP - NEMA	ght angle outlets le transformer without covering remaining outlets, accepts up to 4 transformers total V)
Outlet quantity / type Outlet Type Single row of right Transformer accommodation INPUT Nominal Input Voltage(s) Supported Recommended Electrical Service Input connection type Input cord length (ft.) 7 x NEMA 5-15 7 x NEMA 5-15 7 x NEMA 5-15 1 20V of right 1 20V AC 1 20V (110-125) 1 20V (110-125) 1 20V (110-125)	ght angle outlets le transformer without covering remaining outlets, accepts up to 4 transformers total V)
Outlet Type Single row of right Transformer accommodation Supports 1 larg INPUT Nominal Input Voltage(s) 120V AC Supported 120V (110-125) Recommended Electrical Service NEMAP - NEM Input cord length (ft.) 6	ght angle outlets le transformer without covering remaining outlets, accepts up to 4 transformers total V)
Transformer accommodation INPUT Nominal Input Voltage(s) Supported Recommended Electrical Service Input connection type NEMAP - NEM Input cord length (ft.) Supports 1 large 120V AC 120V AC 120V (110-125) 6	e transformer without covering remaining outlets, accepts up to 4 transformers total V)
INPUT Nominal Input Voltage(s) Supported Recommended Electrical Service Input connection type NEMAP - NEM Input cord length (ft.) 6	V)
Nominal Input Voltage(s) Supported Recommended Electrical Service Input connection type NEMAP - NEM Input cord length (ft.) 120V AC 120V (110-125) 120V (110-125) 120V (110-125) 120V (110-125)	
Recommended Electrical Service 120V (110-125) Input connection type NEMAP - NEM. Input cord length (ft.) 6	
Input connection type NEMAP - NEM. Input cord length (ft.) 6	
Input cord length (ft.) 6	A5-15P
lanut and lanuth (m)	
Input cord length (m) 1.83	
Input cord gauge, type 14 AWG, 3 CO	ND, SJT
Voltage compatibility (VAC) 120	
Maximum Surge Amps 72000	
LEDS ALARMS & SWITCHES	
LED Indicators Protected (Green	en)" & Always On Receptacle (Red)
Switches 1 x Lighted Mas	ster Switch & 6 x Lighted Receptacle Switches
SURGE / NOISE SUPPRESSION	
AC suppression joule rating 1080	
AC suppression response time < 1 ns	
Protection modes Includes full no	rmal mode (H-N) and common mode (N-G / H-G) line surge suppression.
Clamping voltage (RMS) 150	
UL1449 let through rating 400v	
EMI / RFI filtering Up to 40dB	
PHYSICAL	
Shipping weight (lbs) 1.76	
Shipping weight (kg) 0.80	
Unit Dimensions (HWD/in) 1.40 x 3.40 x 15	5
Unit Dimensions (HWD/cm) 3.56 x 8.64 x 38	8.1
Shipping Dimensions (HWD/in) 17.2 x 4.24 x 2	
Shipping Dimensions 43.69 x 10.77 x (HWD/cm)	5.08

Unit weight (lbs)	1.54
Unit weight (kg)	0.70
Material of construction	Plastic
Integrated keyhole mounting tabs	Keyhole mounting slots enable wall mounting
AC line cord color	Cool Gray
Style	Strip
SPECIAL FEATURES	
Green & high efficiency features	Individually controllable outlets
CERTIFICATIONS	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$25,000 Ultimate Lifetime Insurance

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4983.

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.