



## TS5261 - Wireless Synchronized Digital Clock



TS-ACC-002

TS-ACC-003


### Key Features:

- Viewing Distance of 100'
- Automatic Daylight Saving Time Adjustment
- Non-Glare Acrylic Lens
- Quick Correction for Time Change (1-3 Minutes)
- Flush Mount, Does Not Require Back Box
- AC Power Operated
- AM/PM Indicator

The TS5261 Wireless Synchronized Digital Clock is designed with a highly visible 2.5" LED four-digit display for the hours/minutes and a 1.8" LED two-digit display for the seconds.

The TS5261 receives a wireless time signal transmitted daily by a main wireless paging controller, such as the VS4800. The TS5261 uses the time signal to automatically adjust itself, if necessary, to ensure accurate and synchronized time throughout the entire facility.

The TS5261 matches a wide variety of applications and provides years of maintenance-free service.



### Options, Accessories and Complementary Products:

Part Number	Description
TS-OPT-010	Wireless Count Down Timer for Digital Clock
TS-ACC-002	Dual Face Bracket for Digital Clock - Wall Mount
TS-ACC-003	Dual Face Bracket for Digital Clock - Ceiling Mount

### Specifications:

Dimensions	18.23" x 6.22" x 1.5" (W x H x D)	Digit Count, Size & Color	6 Digits, 2.5" High, Red
Weight	4 lbs.	Frequency	VHF (148 - 174 MHz), UHF (400 - 470 MHz)
Power	12V DC / 2A (Using 100-240V AC)	Paging Format	POCSAG, Narrow Band
Operating Temperature	17° - 140°F	Synchronization	Instantaneous
Humidity	0% - 95%, Non-Condensing	Receiver Sensitivity	10u V/M
Frame and Lens	Black Aluminum Frame, Red Diffused Acrylic Lens	Limited Warranty	One Year Parts and Labor
Viewing Distance	100 ft.		

\*Specifications Are Subject to Change Without Notification