



TS4144 - Wireless 14" Synchronized Analog Clock



designed with an easy-to-read dial face, durable frame and tamperproof Plexiglass lens.

The TS4144 receives a wireless time signal transmitted daily by a

The TS4144 Wireless 14" Synchronized Analog Clock is


main wireless paging controller, such as the **VS4800**. The TS4144 uses the time signal to automatically adjust itself, if necessary, to ensure accurate and synchronized time throughout the entire facility.

The TS4144 does not require any wiring and is ideal for renovation projects and new installations.

The TS4144 matches a wide variety of applications and provides years of maintenance-free service.

Key Features:

- Viewing Distance of 100'
- Automatic Daylight Saving Time Adjustment
- Tamper-Proof Plexiglass Lens
- Quick Correction for Time Change (1-3 Minutes)
- Flush Mount (Does Not Require Back Box)
- Battery Operated (Optional AC Power Adaptor)
- Customized Logo Option



Options, Accessories and Complementary Products:

| Part Number | Description | | | |
|-------------|---|--|--|--|
| TS-OPT-003 | 24-Hour Clock Face | | | |
| TS-OPT-004 | Customized Analog Clock Face | | | |
| TS-OPT-005 | Sealed Analog Clock | | | |
| TS-OPT-007 | 110 V AC Adaptor (Replaces Original Clock Batteries, Requires 1.5" Minimum Recessed Power Outlet) | | | |
| TS-OPT-011 | Red Second Hand | | | |

Specifications:

| · | | | | |
|-----------------------|--|----------------------|--|--|
| Dimensions | 13.6" x 2" (W x D) | Dial Face | 12.5", White | |
| Weight | 2.3 lbs. | Frequency | VHF (148 - 174 MHz), UHF (400 - 470 MHz) | |
| Power | Two C Sized Batteries Optional AC Power (AC-DC Adaptor) | Paging Format | POCSAG, Narrow Band | |
| Operating Temperature | 32° - 120°F | Synchronization | 1 Time/Day (Optional 6 Times/Day, User Selectable) | |
| Humidity | 0% - 95%, Non-Condensing | Receiver Sensitivity | 10u V/M | |
| Frame and Lens | Polycarbonate Durable Frame, Plexiglass Lens | Limited Warranty | One Year Parts and Labor | |
| Viewing Distance | 100 ft. | | | |

^{*}Specifications Are Subject to Change Without Notification

