



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: TLP74TG

7 outlet, 4-ft cord, 1400 joules, Timer-controlled ECO-SURGE Home/Office Surge Suppressor



Highlights

- Want to save \$30/year on your energy bill? [Learn how.](#)
- Timer-controlled outlets
- Two separate outlet banks
- 1400 joules
- 7 outlet / 4-ft cord
- Diagnostic LEDs
- \$75,000 Ultimate Lifetime Insurance (USA and Canada only)

Description

Want to save \$30 per year on your energy bill? [Learn how.](#) Tripp Lite's TLP74TG offers reliable, GREEN surge technology that protects your computer and peripherals as well as the environment and your wallet. Energy-saving outlet configuration reduces energy waste (phantom loads) by cutting AC power to unused peripherals. Convenient, multiple programmable timers allow users to set the exact time a device is turned on and off. The unit has 2 separate banks of outlets so you can program up to 20 timer options. The TLP74TG has 7 total outlets, 4 foot cord and diagnostic LEDs to warn of wiring problems and suppressor damage. Network-grade AC suppression rated at 1400 joules shields equipment from surges and line noise. Designed with an attractive cool gray suppressor housing, the TLP74TG provides 1 designated transformer outlet but can accommodate up to 4 transformer plug outlets offering convenient protection of desktop computer equipment and accessories. \$75,000 connected equipment insurance (USA and Canada Only).

Applications

- Perfect for small-to-medium home/business, lighting installations, entertainment systems, satellite and A/V receivers, DVD/CD players and more

Package Includes

- TLP74TG ECO-SURGE Home/Business Theater Surge Suppressor
- Instruction manual with warranty information

Features

- Energy-saving outlet configuration reduces energy waste (phantom loads) by cutting AC power to unused peripherals
- Programmable timer controls the output based on user settings. The timer can be set to automatically power connected ON and OFF based on time of day and day of the week for up to 20 possible timer settings.
- Two sets of timer-controlled outlet banks allow the user to connect equipment with varying timer settings.
- 1400 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- 7 surge-protected NEMA 5-15R AC outlets safeguard and entire home/business theater system while accommodating up to 4 large transformers
- 2 diagnostic LEDs alert user to protection and grounded status
- Lighted on/off switch with integrated circuit breaker - protects against dangerous system overload
- \$75,000 connected equipment insurance (USA and Canada Only)

Specifications

OVERVIEW

Intended Application	Green (Energy Saving)
OUTPUT	
Output Volt Amp Capacity (VA)	15
Output Watt Capacity (watts)	1875
Frequency compatibility	60 Hz
Outlet quantity / type	7 NEMA 5-15R
Outlet Type	NEMA 5-15R
Transformer accommodation	1 Designated transformer outlet but can accommodate up to 4
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	120V (110-125V)
Input connection type	NEMAP - NEMA5-15P
Input cord length (ft.)	4
Input cord length (m)	1.22
Input cord gauge, type	14 AWG 3C SJT
Voltage compatibility (VAC)	120
Maximum Surge Amps	19500
LEDS ALARMS & SWITCHES	
LED Indicators	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
Front panel LCD display	AM/PM LCD Clock
Switches	Combination AC circuit breaker and 2 position lighted on/off power switch
SURGE / NOISE SUPPRESSION	
AC suppression joule rating	1400
AC suppression response time	< 1 ns
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression.
Clamping voltage (RMS)	150
UL1449 let through rating	400
EMI / RFI filtering	up to 20dB
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
PHYSICAL	
Shipping weight (lbs)	1.5

Shipping weight (kg)	0.68
Unit Dimensions (HWD/in)	1.56 x 3.54 x 11.22
Unit Dimensions (HWD/cm)	3.96 x 8.99 x 28.50
Shipping Dimensions (HWD/in)	13.4 x 5.51 x 1.96
Shipping Dimensions (HWD/cm)	34.04 x 14.00 x 4.98
Unit weight (lbs)	1.43
Unit weight (kg)	0.65
Material of construction	plastic
AC line cord color	gray
Style	strip
Outlets center to center measurement	Distance between standard outlets = 28.5mm; Distance between standard outlet and transformer outlet = 57mm
SPECIAL FEATURES	
Green & high efficiency features	Schedulable daily hours of economy mode operation
Right-Angle Plug	No
CERTIFICATIONS	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
UL1363 (Power Tap)	UL1363
UL497A (Communications)	UL497A
FCC Part 68 (Communications)	FCC Part 68
cUL / CSA (Canada)	cUL
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$75,000 Ultimate Lifetime Insurance

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4938.

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.