ON-PREMISES LAUNDRY TUMBLE DRYER ST120

PRODUCT SPECIFICATIONS

Cabinet Dimensions	
Width	46 3/8"
Depth	67 15/16"
Height	85.7"
Cylinder Diameter	44"
Cylinder Depth	41"
Drying Capacity	120 lb
Cylinder Volume	36.1 cu.ft.
Door Opening Size	26 7/8"
Operation	
Motor HP	Fan: 1 HP, Cylinder: 3/4 HP;
Energy Data	
Gas Models - Per Pocket	270,000 Btu/hr
Steam Models - 100 psi	At 100 psi: 11.7 BHP, 405,000 Btu/hr;
Airflow	
Airflow	60 Hz: 1600 CFM
Plumbing Connections	
Gas Models	3/4"
Steam Models	3/4"
Shipping	
Net Weight	Gas: 1275 lb; Steam: 1375 lb;
Shipping Weight	Gas: 1338 lb; Steam: 1446 lb
Shipping Width	48 1/2"
Shipping Depth	72″
Shipping Height	90″
Agency Approvals	
Gas Models	CSA, CE, Australia Gas
Steam Models	CSA, CE

FEATURES & BENEFITS

- Precise drying performance with OPT (Over-Dry Prevention Technology).
- Concentrated airflow pattern and sealed cylinder rims ensure maximum air utilization and energy savings.
- Large, easy to clean lint compartment.
- Fewer moving parts mean fewer maintenance problems and less wear.
- High performance heater box increases energy efficiency, reduces drying times and provides more comfortable operating environment.



AVAILABLE CONTROLS

Control Quantum Gold



Description

Quantum Gold offers the flexibility of 30 programmable cycles combined with the accuracy of our moisture sensing technology (OPT) that prevents over drying, saving time and energy.

Dual Digital



Set drying time, temperature and cool down. Features include one touch cycle repeat, automatic extended tumble and large digital countdown display.

ELECTRICAL SPECIFICATIONS

Gas and Steam		
Voltages	Amps	
200-208/240/60/3	7.7	
460-480/60/3	3.9	

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO#9001:2000.

