



TUMBLE DRYERS

Uncomplicated. Uncompromising. Unmatched. Enjoy heavy-duty construction that will provide reliable operation for years to come.

Our single pocket tumble dryers feature a concentrated airflow pattern and sealed cylinder rims to ensure maximum air utilization and energy savings. This superior drying performance helps laundries maximize throughput to meet the daily workload without the need for added shifts or costly overtime. Our tumble dryers are designed with fewer moving parts, so that you'll face fewer maintenance problems and less wear and tear. We make it even easier with a large, easy-to-clean lint compartment and a heavy-duty door hinge designed to withstand heavy usage.



FEATURES

High-performance heater box increases energy efficiency, reduces drying times and provides a more comfortable operating environment

A reversing cylinder helps eliminate tangles of large items such as sheets and blankets, ensuring even drying and easy removal of loads at cycle completion

The Combustion Auto Response Equipped (C.A.R.E.) system alerts you to abnormally high temperatures in the cylinder and automatically sprays water in the cylinder to cool it down if necessary

The 55 lb (24.5 kg) capacity model also fits through a 36 inch (914 mm) door opening and is a foot shorter than our 50 lb (22.6 kg) unit, making it a great replacement option for laundries short on space

Available Over-dry Prevention Technology eliminates the costs associated with over-drying

Available in 25 lb (11.3 kg), 30 lb (13.6 kg), 35 lb (15.9 kg), 50 lb (22.6 kg), 55 lb (24.5 kg), 75 lb (34.0 kg), 120 lb (54.4 kg) and 170 lb (77.1 kg) capacities

TUMBLE DRYER CONTROLS

QUANTUM™

This control allows you to choose from a variety of selectable dryness levels, vary your temperature and drying time with Time Dry, or create custom cycles by selecting Special Cycle or Special Time.

DUAL DIGITAL

With features that include one touch cycle repeat, automatic extended tumble and a large digital countdown display, it's simple to set your drying time, temperature and cool down.