# ON-PREMISES LAUNDRY TUMBLE DRYER ST055

## PRODUCT SPECIFICATIONS

Cabinet Dimensions	
Capacity	55 lb
Width	34 1/2"
Depth	53 5/8″
Height	66 3/4"
Cylinder Diameter	33"
Cylinder Depth	35″
Cylinder Volume	17.3 cu. ft.
Door Opening Size	26 7/8"
Energy Data	
Gas Models - Per Pocket	112,000 Btu/hr
Steam Models - 100 psi	N/A
Electric Models	27 kW
Connections	
Gas	1/2" NPT
Plumbing Connections - Steam	N/A
Air Outlet	8″
Motor	
Fan	1/2 HP
Cylinder	1/2 HP
Airflow	
Airflow	700 cfm
Shipping	
Net Weight	Gas/Steam: 435 lb Electric: 435 lb
Shipping Weight	Gas/Steam: 476 lb Electric: 476 lb
Shipping Width	35 1/2"
Shipping Depth	59"
Shipping Height	72"
Agency Approvals	
Gas Models	CSA
Electric and Steam Models	CSA

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO#9001:2000.

#### **FEATURES & BENEFITS**

- Large, easy to clean lint compartment.
- Fewer moving parts mean fewer maintenance problems and less wear.
- High performance heater box increases energy efficiency, reduces drying times and provides more comfortable operating environment.
- Fits through 36 inch door opening and is a foot shorter than our 50 lb unit, making it a great option for laundries short on space.
- Fast drying results, outperforming our 50 lb tumbler in speed and efficiency.
- Concentrated axial airflow pattern and sealed cylinder rims ensure maximum air utilization and energy savings.



### **AVAILABLE CONTROLS**

## Control


Quantum Gold



#### Description

Quantum Gold offers the flexibility of 30 programmable cycles.

**Dual Digital** 



Set drying time, temperature and cool down. Features include one touch cycle repeat, automatic extended tumble and large digital countdown display.

#### **ELECTRICAL SPECIFICATIONS**

Gas	
Voltages	Amps
200-208/240/60/3	4/3.9
120/208-240/60/1	9.2/6.5

Electric	
Voltages	Amps
200-208/60/3	79
208/60/1	129
240/60/1	115
240/60/3	65

