



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



# FLUSH NON-RATED - Plastic Access Door PA-3000

## Application

- Easy access to walls and ceilings
- Economical and attractive

## Product Features

- High impact styrene plastic with U.V. stabilizers
- Hinged with a removable feature

## PA-3000 Access Door Specifications:

**Door / Door Frame:** 1/8" high impact styrene plastic with U.V. stabilizers  
 Flush to frame — rounded safety corners, one piece outside flange with 3/4" deep mounting frame

**Standard Latch:** Snap latches allow door to fit tightly within frame

**Door Hinge:** Concealed

**Finish:** White, with textured exposed surfaces




## AVAILABLE SIZES (Special sizes available upon request)

NOMINAL DOOR SIZE W X H		WEIGHT PER DOOR	
inches	mm	lbs.	kg.
4 X 6	101 X 152	1/2	1/4
6 X 9	152 X 228	1/2	1/4
8 X 8	203 X 203	1/2	1/4
12 x 12	305 x 305	1/2	1/4
14 X 14	356 X 356	3/4	1/3
14 X 29	358 X 735	4	1-7/8
18 x 18	457 x 457	2-1/4	1
22 X 22	560 X 560	4	1-7/8

Wall or ceiling opening is  $W + 1/4"$  ( 6 mm)

For detailed specifications see submittal sheet



PA-3000 View of door back