# LRA

## 10 Series - Microphone Adapter Cables

10-140-5	5 ft.
10-140-10	10 ft.
10-140-15	15 ft.
Female XLR to 1/4" mo	ono plug.
Black PVC jacketed ca	
Above wired: Pin 1 & 3	8 - ground
Pin 2 - hot.	



3 ft



10-141-5	5 ft.
10-141-10	10 ft.
10-141-15	15 ft.
Male XLR to 1/4" mond	o plug.
Black PVC jacketed ca	
Above wired: Pin 1 & 3	3 - ground
Pin 2 - hot	



10-149-3	3 ft.
10-149-6	6 ft.
<b>10-149-10</b> 1	0 ft.
<b>10-149-15</b> 1	5 ft.
Male XLR to 1/4" stereo plug.	
Black PVC jacketed cable, shie Above wired: Pin 1-ground Pin	



10-142-5.....5 ft. **10-142-10**.....10 ft. 10-142-15.....15 ft. Female XLR to RCA Male plug. Black PVC jacketed cable, shielded.


Above wired: Pin 1 & 3 - ground



## 10-150

Pin 3-ring

10\_148\_3






### 10-150A

High quality 8mm "OFC" version of 10-150 cable length: 6.5 inches.



### **10-143-5**......5 ft. **10-143-10**.....10 ft. 10-143-15.....15 ft.





#### 10-151

XLR "Y" cable, one Female to two Males. Black PVC jacketed cable, shielded. Above wired Pin to Pin. Cable length is 3 inches



#### 10-151A

High Quality 8mm "OFC" version of 10-151 Cable length: 6.5 inches.




#### 10-144

Pin 2 - hot.

Female XLR to 3.5mm mono plug, 6 ft.

10-145	6ft.
10-145-1	1ft.
10-145RT-1	1ft. (right angle plug)
Female XLR to 3.5m	m stereo plug.
Black PVC jacketed	cable shielded



XLR "Y" cable, two 3-pin XLR Females to a 3.5 mm stereo plug. 6 ft. long. Black Above 3.5mr Tip....

G 0.0 0.0.0.	, b.a.g. aag.	4
Black PVC jack	eted cable, shielded.	25
Above wired Pir	n to Pin.	9
3.5mm Male	XLR Female	
Tip	Pin 2	-
Ring	Pin 3	
Sleeve	Pin 1	



### 10-146

Male XLR to 3.5mm mono plug, 6 ft. long. Black PVC jacketed cable, shielded. Above wired: Pin 1 & 3 - ground / Pin 2 - hot.



#### 10-153-1

Female XLR to two RCA Male plugs. Y cable, 1 ft. long. Uses flat style black PVC jacketed cable, shielded. Above wired: Pin 1-ground Pin 2-tip (hot) RCA plug Pin 3-tip (hot) RCA plug



Male XLR to 3.5mm stereo plug, 6 ft. long. Black PVC jacketed cable, shielded. Above wired: 3.5mm tip to XLR pin 2 3.5mm sleeve and ring to XLR Pin 1 & 3 - ground