

CALRAD

40 Series - Converters/Baluns

40-CW01A Designer Style Composite Video + Stereo Audio Wallplate Balun

Composite video and stereo audio over Cat5e extender on a designer style insert. Passive balun wall plate allows you to send composite video and stereo audio up to 1000 feet over a single Cat5e UTP cable. No power required. Dimensions: 11.5mm X 71mm. Sold in pairs.

1 x RJ45 Jacks



40-VW01

VGA over Cat5e extender on a designer style insert. Passive balun wall plate allows you to send VGA up to 300 feet over a single Cat5e UTP cable. Supports resolutions up to 1280 X 1024 No power required. Dimensions: 11.5mm X 71mm. Sold in pairs.

1 x RJ45 Jacks



40-DA01 Balanced Passive Signal Converter

40-DA02 Balanced Passive Signal Converter with 4" wire pigtail

Passive bi-directional signal design using UTP Cat5e or Cat6 cable pair. Use for Audio/Video/Component/IR signals.

Cable Distance:

Analog Audio, 1000 ft. Digital Audio, 300 ft. IR Signals, 300 ft. Composite video, 1000 ft., High Definition 480P - 300 ft., 720P - 200 ft., 1080i -100 ft., 1080P - 50 ft.

Wire Termination

40-DA01: 2 Conductor captive screw terminals

40-DA02: 2 conductor locking style punch down blocks for easy wire

Specifications

Bandwidth: DC to 50Mhz, DC passive

Connectors: RCA Male Plug


Signal Types: Analog+Digital Audio \ Video \ IR Signals

Housing Material: Plastic, Color: Black

Dimensions: 1.76"(L) x .68"(W) x .68"(H)

Dimensions: L 1.32" x W 0.6" x H 0.6"


40-DA01 Male RCA Plug spacing .64 inch center to center



95-1041 VIDEO BALUN CAT-5 CABLE SYSTEM

Balanced video RJ45 to unbalanced Male BNC adapter. Transmit a composite video signal up to 1000' using industry CAT-5 networking cables with RJ45 connectors. Includes CAT 5 RJ45 Male to 2 screw terminal adapter. The advantages of this type of system are clear video signal, fewer cables to manage, lower cost per connection, centralized wiring for greater control. Video bandwidth 12MHz. Two units required for transmission and reception of balanced signals Size: Width .76" x Height .9" x Depth 2".

1 x RJ45 Jacks



95-1046 Composite Video, S-Video, Analog or Digital Audio Balun

This passive RCA Audio/Video balun is ideal for corporate A/V, schools or home theater applications. Transmit stereo audio, digital audio, composite video or S-Video over A single Cat 5/Cat 6 UTP cable up to 1000 feet. Transmission of S-Video requires the Calrad 55-741 S-video Y adapter cable sold separately.

Specifications:

RCA input Connectors: Gold plated RCA jacks X 2

RJ45 Connector : Female RJ45 jack X 1

Signal Input: Stereo Audio, Digital Audio, Composite Video, S-Video

Cable Transmission Distance: Stereo audio 2500 Feet max, Digital audio 1000 feet max

Dimensions: Length: 2.4" X Width: 1.69" X Height .865"

1 x RJ45 Jacks

