

CALRAD

95 Series - Touchscreens

10.4" TOUCH SCREENS

- 95-1062-BK (Black USB)
- 95-1062-BK-KIT (INWALL KIT, BLACK TRIM PANEL)
- 95-1062-WH (White USB)
- 95-1062-WH-KIT (INWALL KIT, WHITE TRIM PANEL)
- 95-1062BK-RS232 (BLACK RS232)
- 95-1062WH-RS232 (WHITE RS232)

The 95-1062 series touchscreens can be used on a desktop or in-wall applications. Perfect for use with point of sale products or home automation control systems. Easy to setup driver software, available in USB or RS232 interfaces. Adjustable arm for screen tilt and height. Using the optional in-wall kits the screen can be located inside a wall. OSD (Onscreen Display) for Brightness, Contrast, Color, Image settings, Audio. Front panel power, input selection buttons. Video inputs, VGA, Composite Video 1, Composite Video 2. Use Calrads 72-130 adapters to extend RS232 control signals up to 200 ft.. Use USB balun devices on page 155 to extend the USB version. Use Calrad VGA baluns to extend the video signal over 100 ft., see page 85.


Specifications:

- 4-wire resistive Touchscreen (optional): USB or RS232 interface
- VGA input: 15 pin D-SUB analog
- RGB interface PAL/NTSC color system
- High resolution- up to 1024x768 (H x V) formatted
- Automatic display adjustment
- High-Brightness CCFL Backlight
- 2 RCA video inputs, 1 Audio Input, 1 Audio output
- On Screen Display menu control (Multi-language)
- Full-function infrared remote control
- Built-in 2 Watt Amplifier and Speaker
- Screen Size: Diagonal 10.4"
- Dot Resolution (RGB): 800(H) x 600(V) = 1,440,000 (dots)
- Viewing Angle: 100 degrees/75 degrees (H/V)
- Aspect Ratio: 4:3
- Contrast: 500:1
- LCD Brightness: 170cd/m2
- Viewing Angle: 45/60(U/D), 65/65(L/R)
- Operating Voltage: DC 11-13V
- Power Consumption: <10W
- Dimension (mm): 252W x 185H x 267D
- Weight (kg): 1.5
- Colors: Black, White

Accessories:

- VGA Cable: 1 Piece
- Audio Signal Cable(Black): 1 Piece
- Video Signal Cable(Yellow and Buff): 2 Pieces
- 12Vdc 1.5 Amp power supply: 1 Piece
- Remote Control: 1 Piece
- PC Driver Disk: 1 Piece
- Operation Manual: 1 Piece

Note: All specifications on this page are subject to change without notice



95-1062 INWALL BRACKET KIT



72-130 SERIAL CAT5E ADAPTERS

Connect RS232 devices using standard UTP Cat5e cable. Distances of over 200 ft. at 9600 baud can be achieved.



3 Piece kit includes 2 - DB9 Male to RJ45 adapters, 1- gender changer

Visit Calrad on the web at: www.calrad.com