CALRAC

75 Series - RF Connectors, Mini UHF, N, SMA

Technical drawings and specifications are available for these products. Please ask your Calrad sales representative for details

MINI UHF CONNECTORS & ADAPTERS



75-615 Mini UHF Male crimp connector, 3 piece for RG 58, nickel plated.

75-615-BK

Black Version.



75-616 Mini UHF Female coupler. Overall length: 1.29".



75-617 Mini UHF Male to Female right angle coupler.



75-618 Mini UHF Male crimp connector, 2 piece for RG 58.



75-570 Male "N" connector for RG-8/11, 213/214.



75-571 Double Female "N" connector.



75-572 Chassis mount Female "N" connector. Over all length is 1.09". Mounts in chassis .62" hole.



75-573 BNC Male to "N" Female. 75-575 BNC Female to "N"



75-574 "F" Female to "N" Male connector.



75-576 PL-259 Male to "N" Female connector.



75-577 UHF Female to "N" Male.



75-640 Male to Male "N" connector.



75-641 Female to Male right angle "N" connector.



75-642 "T" adapter, Female "N" to Male "N" to Female "N".



75-760 Male SMA connector for RG58A. Nickel plated brass construction, gold plated contacts with teflon insulator.



75-761 Male SMA connector for RG59/62. Nickel plated brass construction, gold plated contacts with teflon insulator.



75-762 RG58A 75-763 RG59/62 Male SMA 3 piece crimp connector for. Nickel plated brass construction. gold plated contacts with teflon insulator.



75-764 Female SMA 3 piece crimp connector for RG58A. Nickel plated brass construction, gold plated contacts with teflon insulator.



75-765 Female SMA 3 piece crimp connector for RG59/62. Nickel plated brass construction, gold plated contacts with teflon insulator.



75-766 BNC jack to SMA plug. Nickel plated brass construction, gold plated contacts with teflon insulation.



75-767 Male to Female SMA Right Angle inline adapter.



75-768 Female to Female SMA inline adapter. Nickel plated brass construction, gold plated contacts with teflon insulator.



Visit Calrad on the web at: www.calrad.com