

75 Series - Video RF Connectors

BNC CONNECTORS & ADAPTERS . . . continued

Please Note: For 75-533-PS & 75-534-PS Series, images and specifications are subject to change



Right Angle Water Resistant Compression Style Connectors
Nickel Version
 75-533-PSBNCRA RG59
 75-534-PS-BNCRA RG-6
Gold Version
 75-533G-PSBNCRA RG59
 75-534G-PSBNCRA RG-6



Water Resistant Compression Style Connectors
Nickel Version
 75-533-PS-BNC RG59
 75-534-PS-BNC RG-6
Gold Version
 75-533G-PS-BNC RG59
 75-534G-PS-BNC RG-6
75-534Q-PS-BNC
 Quad Shield RG-6 Version



75-645
 50 Ohm BNC Female inline connector for RG-59. 3 piece crimp.



75-646
 RG-59 crimp BNC Female 2 piece.



75-566
 Inline BNC Female solderless screw on adapter for RG-58.



75-559-75
 75 ohm version
75-559
 50 ohm version Solderless BNC Male right angle connector for use with RG-59 coax cable. Cable opening .24". Black snap style plastic body.



75-559-ST-75
 75 ohm version
75-559-ST
 50 ohm version Solderless BNC Male connector for use with RG-59 coax cable. Cable opening .24". Black snap style plastic body.



75-554
 BNC right angle crimp connector for RG-58. 2 pcs.



75-561
 BNC Male to BNC Female right angle adapter.
75-693
 75 ohm version.



75-526
 BNC Female to "F" Female.



75-527
 BNC Male to "F" Male.



75-517
 "F" Female to BNC Male adapter.
75-517G
 Gold version.
75-679
 75 ohm version.



75-540
 "T" adapter, 2 BNC Females to 1 BNC Male.
75-690
 75 ohm version.



75-541
 BNC "T" with 3 Female BNC connectors.
75-691
 75 ohm version.



75-620
 4-way BNC "T" Connector, with 3 Females to 1 Male.




75-621
 3-way BNC "T" BNC Male connectors.



75-622
 3-way BNC "T" Connector, with 2 Males to 1 Female.



75-623
 BNC "T" Connector, with 1 Male to 2 Females.



75-624
 BNC "U" adapter, with 1 Male to 2 Females. U shape.



75-628
 Isolated BNC feed thru. True 75 ohm. Overall length 1.29". Mounts in .5" D hole.
75-628-50
 50 Ohm Version



75-552
 BNC feed thru double Female panel mount. Mounts in .5" D hole. Overall length is 1.28". Bushing length .33".
75-696
 75 ohm version



75-521
 Panel feed thru connector. BNC Female to RCA Female. Bushing dia.: .487" Bushing length: .33" Overall length is 1.29" Mounts in .5" hole. 75 ohm.
75-521-50
 50 Ohm version



75-543
 BNC Female chassis connector. Overall length is 1.08". Mounts in .375" chassis hole. Bushing length .28".
75-543G
 Gold version.
75-697
 75 ohm version.



75-521-3/8
 Panel feed thru connector. BNC Female to RCA Female. Bushing dia.: .365" Bushing length: .27" Overall length is 1.06". Mounts in .375" hole.