


# CALRAD

## 55 Series - Component, Audio-Video Cables


### 5 RCA MOLDED MALES TO 5 RCA MOLDED MALES, SHIELDED, GOLD PLATED CONNECTORS

55-611-RCA-3	3 ft.
55-611-RCA-6	6 ft.
55-611-RCA-10	10 ft.
55-611-RCA-12	12 ft.
55-611-RCA-15	15 ft.
55-611-RCA-20	20 ft.
55-611-RCA-25	25 ft.
55-611-RCA-35	35 ft.
55-611-RCA-50	50 ft.
55-611-RCA-100	100 ft.



### 55-510 SHIELDED RGB + SYNC HDTV CABLE

This cable is used for HDTV applications. Terminated with 5 high quality gold plated RCA connectors with chrome bodies and color coded rubber finger grips, specifically designed to minimize signal loss. For RGB+HV or RGB + Audio (Y,Pb,Pr + Audio), signal delivery. Silver plated cable for accurate signal transfer. Overall cable O.D. .37". Individual cable O.D. .1".



55-510-6	6 ft.
55-510-10	10 ft.
55-510-12	12 ft.

### SHIELDED RGB VIDEO CABLES

(3) BNC Males to (3) BNC Males Comes with 75 ohm nickel plated connectors. Cable O.D. .525",

55-610-3	3 ft.
55-610-6	6 ft.
55-610-10	10 ft.
55-610-12	12 ft.
55-610-15	15 ft.
55-610-25	25 ft.
55-610-33	33 ft.
55-610-35	35 ft.
55-610-50	50 ft.
55-610-100	100 ft.
55-610-500	500 ft.



### 55-618 LOW LOSS MULTI-CONDUCTOR (RGB+HV, STEREO AUDIO) SHIELDED COAX AUDIO/VIDEO CABLE. SUPPORTS STANDARD DEFINITION AND HDTV.

7 Individually molded, color coded cables. 5 x True 75 Ohm BNC's (RGB + HV) video Male plugs. 2 x RCA stereo analog audio Male plugs (1 ea. Black barrels with Red & White bands). Overall cable O.D. .44", Individual cable O.D. .12", individual cable lengths from strain relief 8". Available in 6,12 & 25ft. lengths.



### SHIELDED RGB VIDEO CABLES

(5) BNC Males to (5) BNC Males Comes with 75 ohm nickel plated connectors. Cable O.D. (.65").

55-611-3	3 ft.
55-611-6	6 ft.
55-611-10	10 ft.
55-611-12	12 ft.
55-611-15	15 ft.
55-611-20	20 ft.
55-611-25	25 ft.
55-611-50	50 ft.
55-611-100	100 ft.
55-611-250	250 ft.
55-611-500	500 ft.



### 55-509 5.1 SHIELDED DIGITAL AUDIO CABLE for SACD, DVD-AUDIO, and SURROUND SOUND SYSTEMS

Interface cable between DTS, digital sound processors, digital processor based DVD players to amplifiers/receivers. Easy to read ID channel labels. 6 RCA plugs both ends. Overall cable O.D. (.435"). Individual cable O.D. (.103").

55-509-6	6 ft.
55-509-12	12 ft.



### 55-616 LOW LOSS MULTI-CONDUCTOR (COMPONENT VIDEO, COMPOSITE, SVHS, STEREO ANALOG, DIGITAL AUDIO) SHIELDED COAX AUDIO/VIDEO CABLE. SUPPORTS STANDARD DEFINITION AND HDTV.

9 Individually molded, color coded cables, grouped & labeled. 1 x RCA composite video Male plug (Yellow), 1 x SVHS molded Male plug, 3 x RCA component video plugs (Y=Green, Pb=Blue, Pr= Red), 4 x each RCA stereo analog audio Male plugs (2 ea. Red & White, 2 stereo audio channels), 1 x RCA Digital audio Male plug (Orange). This cable can be used for stand alone audio & video signal delivery or for Calrad's 40-934B 1 x 5 HDTV distribution amplifiers. Overall cable O.D. 1.0", Individual cable O.D. (.2"), individual cable lengths from strain relief 11".



### Lengths Available

55-616-6	6 ft.	55-616-12	12 ft.	55-616-25	25 ft.
----------	-------	-----------	--------	-----------	--------