

CALRAD

40 Series - Switches


MINIATURE CIRCUIT BOARD MOUNTING SWITCHES

Right angle mounting - $\frac{5}{16}$ " long threaded bushing. Contact rating 6 Amp, 125 Vac. All mount in $\frac{1}{4}$ " hole.
40-502 DPDT On-On
40-503 DPDT On-Off-On
 Body Size: $\frac{1}{2}$ " x $\frac{1}{2}$ " x $\frac{3}{4}$ " deep including terminals



MINIATURE CIRCUIT BOARD MOUNTING SWITCHES

Printed circuit mounting - $\frac{5}{16}$ " long threaded bushing. Contact rating 6 Amp, 125 Vac. All mount in $\frac{1}{4}$ " hole.
40-521 SPDT On-Off-On
 Body Size: $\frac{1}{2}$ " x $\frac{5}{16}$ " x $\frac{5}{16}$ " deep including terminals
40-523 DPDT On-Off-On
 Body Size: $\frac{1}{2}$ " x $\frac{1}{2}$ " x $\frac{5}{16}$ " deep including terminals




SUB-MINIATURE TOGGLE SWITCHES

40-610 SPDT-ON/ON, 10 Amp, 125 volt (non-inductive load), solder-type terminals. Body size: $\frac{5}{16}$ " x $\frac{1}{2}$ " x $\frac{9}{16}$ ".
40-611 DPDT, 10 amp, 125 volt (non-inductive load), solder-type terminals. Body size: $\frac{1}{2}$ " x $\frac{1}{2}$ " x $\frac{1}{2}$ ".
40-612 DPDT, center-off. Contact 5 Amp, 125 volt current cap. AC (non-inductive load). Body size: $\frac{1}{2}$ " x $\frac{1}{2}$ " x $\frac{1}{2}$ ".



ULTRA SMALL SUB-MINIATURE TOGGLE SWITCHES


3 Amp, 125 Vac. Chrome handle with red tip for eye-catching indication. $\frac{3}{16}$ " dia. Bushing: $\frac{7}{32}$ " long.
40-608 SPDT-ON/ON
 body size: $\frac{5}{16}$ " x $\frac{3}{16}$ " x $\frac{1}{2}$ " deep including terminals
40-609 DPDT-ON/ON
 body size: $\frac{11}{32}$ " x $\frac{5}{16}$ " x $\frac{1}{2}$ " deep including terminals



MINIATURE CIRCUIT BOARD MOUNTING SWITCHES


Vertical mounting - $\frac{5}{16}$ " long threaded bushing. Contact rating 6 Amp, 125 Vac. All mount in $\frac{1}{4}$ " hole.

40-511 SPDT On-Off-On
 Size: $\frac{1}{2}$ " x $\frac{5}{16}$ " x $\frac{7}{8}$ " deep including terminals
40-512 DPDT On-On
40-513 DPDT On-Off-On
 Size: $\frac{1}{2}$ " x $\frac{1}{2}$ " x $\frac{7}{8}$ " deep including terminals



MINIATURE ECONOMY TOGGLE SWITCHES W/ SILVER PLATED CONTACTS

3A-125 Vac, mounts in $\frac{1}{4}$ " hole size, solder terminals. $\frac{5}{16}$ " long threaded bushing.
40-566 SPDT On-On
40-567 SPDT On-Off-On
 Size: $\frac{1}{2}$ " x $\frac{5}{16}$ " x $\frac{9}{16}$ " deep including terminals
40-568 DPDT On-On
40-569 DPDT On-Off-On
 Size: $\frac{1}{2}$ " x $\frac{1}{2}$ " x $\frac{9}{16}$ " deep including terminals




SUB-MINIATURE TOGGLE SWITCHES

Extra small in size, chrome handles with red tip for quick eye-catching indication, 3 Amp, 125 Vac.
40-613 SPDT-ON/ON
 size: $\frac{7}{16}$ " x $\frac{1}{4}$ " x $\frac{9}{16}$ " deep including terminals
40-614 DPDT-ON/ON
 size: $\frac{7}{16}$ " x $\frac{7}{16}$ " x $\frac{9}{16}$ " deep including terminals Bushing: $\frac{1}{4}$ " dia x $\frac{1}{4}$ " long.




SUB-MINIATURE TOGGLE SWITCH

6 Amp, 125 Vac, $\frac{1}{4}$ " mounting hole. $\frac{5}{16}$ " thread length.
40-699 SPDT-ON/ON
 body size $\frac{3}{4}$ " x $\frac{1}{2}$ " x $\frac{5}{8}$ "
40-700 DPDT-ON/ON
 body size $\frac{7}{8}$ " x $\frac{1}{2}$ " x $\frac{9}{16}$ "



LEVER SWITCHES

6 Amp, 125 Vac, mounts in $\frac{3}{4}$ " round hole. Lever color is red. Lever height is .99"
40-705 DPDT-ON/ON
40-706 SPDT-ON/ON



ROCKER SWITCHES

6 Amp, 125 Vac, mounts in $\frac{3}{4}$ " round hole. Rocker color is white. Size is .7"
40-707 SPDT-ON/ON
40-708 DPDT-ON/ON



40-630 SPST ROCKER SWITCH

Molded plastic, encased with mounting flanges. Mounting centers: $\frac{1}{32}$ "
 Size: $\frac{1}{2}$ " x $\frac{1}{2}$ " x $\frac{7}{8}$ ".
 Rating: 3 amps, 125 volts AC.

