


CALRAD

55 Series - Bulk Audio & Video Cable

COMPONENT, SHIELDED VIDEO CABLE

55-610B, 3 COAX CABLES 55-611B, 5 COAX CABLES

Oxygen free copper "OFC". Miniature shielded 75 ohm video coax cable, red, green, blue, black, white. Multi-stranded tension barring filler for superb strength. Flexible .05" thick black rubber jacket. Overall cable diameter .65", individual coax cable diameter .20". Individual cable dielectric insulation O.D. .118". Nominal capacitance 17pf/ft. Shielding 93% braided copper. Nominal attenuation MHz dB/100'. 100MHz-4.6dB, 400MHz-9.18dB. Nominal velocity of propagation 80%. Use Calrad 75-607, 75-801G-75 75 ohm BNC connectors, 30-291, 30-427, 30-390 RCA connectors. 55-610 Available in 500' spools, 55-611 available in 250' & 500' spools.



55-716B

8mm SHIELDED SILVER PLATED DIGITAL AUDIO VIDEO CABLE

Bulk cable in 250' spools.

Low capacitance, precision 110 ohm construction for sharp and accurate digital signal transfer. Specially designed for excellent performance over long runs. Tightly wound braided shielding resists leakage and outside interference. Weight is 16 lbs. per spool. Cable O.D. .315".



55-612B, 55-866B, SHIELDED HDTV RGB+SYNC VIDEO CABLE


HDTV RGB+SYNC cable color coded red, green, blue, black, and white. Tin plated copper conductors. Low loss miniature 75 ohm coax cables individually shielded and with overall braided shielding plus multi-strand tension barring filler for superb strength. High strand count for accurate signal transfer. Cable overall O.D. .37". Individual cable O.D. .1". Flexible black PVC jacket. Available in spools of 100' & 250 feet. weight of 8.7 lbs. or 250' spools weight of 21.7 lbs. Use Calrad connectors 30-291, 75-801G-75.



55-770GB

MOLDED MINIATURE SHIELDED S-VIDEO CABLE


Dual miniature 75 ohm low loss S-Video cable. OFC braided shields and center conductors. Color coded center conductors for easy signal identification. Black PVC rubber jacket. Overall cable O.D. .23" x .12". Individual cable O.D. .115". Available in 1000' spools.



55-862B

MOLDED COMPOSITE VIDEO/STEREO AUDIO CABLE


Molded video and stereo audio cable available in spools. This cable provides a foil over stranded copper, the audio is copper braided shielding with color coded center conductors for easy signal identification. Black PVC jacket. Overall cable O.D. .49" x .23". Available in 250' spools.



55-771GB

8mm LOW LOSS S-VIDEO CABLE


Color ID for luminance and chrominance signals. Red/white miniature 75 ohm coax cable with thick PVC jacket. Capacitance per foot 16.9pf. Insulation foamed PE. Available in 330' spools. Weight is 19 lbs. per spool. Overall cable O.D. .315", individual cable O.D. .172".



55-705B

SHIELDED 6mm DUAL MOLDED AUDIO CABLE

Triple shielded audio cable available in 250' or 330' spools. This cable is perfect for any stereo audio feed for home theater systems. 2 braided shields and 100% foil coverage. Weight is 19 lbs. per spool. Cable O.D. .47" x .23".



55-868B

MOLDED S-VIDEO & STEREO AUDIO CABLE


Molded S-video and stereo audio shielded cable available in 250' spools. This cable provides 2 miniature 75 ohm shielded video cables for SVHS (chrominance, luminance) and individually shielded cables for L+R audio signals. Black PVC jacket with 95% braided shielding. Overall cable O.D. .517" x .2".



55-715B

8mm DOUBLE SHIELDED VIDEO 'OFC' CABLE

Audio cable available in 500' spools. Thick rubber jacketed audio cable. 100% foil shield with 95% braided 'OFC' oxygen free copper shielding and center conductor. Weight is 25 lbs. per spool. Cable O.D. 8mm, .315".



55-897B

MINIATURE SHIELDED DUAL MOLDED AUDIO CABLE

2 Conductor shielded miniature dual audio cable. Overall cable O.D. .19" x .1". Individual cable O.D. .095". Available in 1000' spools. Weight 8.6 lbs. per spool.

