


Cast Iron Flanged Fittings

Class 125 (Standard)

FIGURE 812 Flanged Reducing Tee 	Size						Unit Weight			
							Black		Galv.	
	NPS	DN	NPS	DN	NPS	DN	lbs	kg	lbs	kg
 Read as: 6 x 5 x 4 (150 x 125 x 100DN)	3	80	2	50	3	80	33.00	14.97	—	—
			3	80	1½	40	32.00	14.51	—	—
					2	50	34.00	15.42	—	—
					2½	65	35.00	15.87	—	—
					4	100	56.00	25.40	—	—
	4	100	2	50	4	100	50.00	22.68	—	—
			2½	65	4	100	56.00	25.40	—	—
			3	80	3	80	53.00	24.04	—	—
					4	100	59.00	26.76	—	—
			4	100	2	50	51.00	23.13	—	—
					2½	65	56.00	25.40	—	—
					3	80	57.00	25.85	—	—
					6	150	88.00	39.91	—	—
	5	125	5	125	3	80	71.00	32.20	—	—
					4	100	80.00	36.28	—	—
	6	150	3	80	6	150	91.00	41.27	—	—
			4	100	4	100	88.00	39.91	88.00	39.91
					6	150	94.00	42.63	—	—
			5	125	4	100	91.00	41.27	—	—
					2	50	86.00	39.00	—	—
			6	150	2½	65	90.00	40.82	—	—
					3	80	92.00	41.72	—	—
					4	100	97.00	43.99	—	—
					5	125	105.00	47.62	—	—
					8	200	142.00	64.40	—	—
			4	100	6	150	140.00	63.49	—	—
					8	200	146.00	66.21	—	—
	8	200	6	150	4	100	125.00	56.69	—	—
					6	150	144.00	65.31	—	—
			8	200	8	200	159.00	72.11	—	—
					3	80	140.00	63.49	—	—
					4	100	143.00	64.85	143.00	64.85
					6	150	156.00	70.75	156.00	70.75
	10	250	8	200	6	150	220.00	99.77	—	—
					8	200	232.00	105.22	—	—
					10	250	262.00	118.82	—	—
			10	250	4	100	225.00	102.04	—	—
					6	150	240.00	108.84	—	—
					8	200	262.00	118.82	—	—
Dimensions for reducing tees for sizes 16" NPS (400 DN) and smaller have same center to face dimensions as straight size fittings corresponding to the largest opening. Dimensions of sizes not listed furnished on request.	12	300	8	200	8	200	298.00	135.15	—	—
					12	300	340.00	154.20	—	—
			12	300	6	150	323.00	146.49	—	—
					8	200	330.00	149.66	—	—
					10	250	362.00	164.17	—	—

Note: See page 62 for pressure-temperature ratings.