



## Cast Iron Threaded Fittings Class 125 (Standard)

FIGURE 383 Hex Bushing	Size					Unit Weight				
	NPS	DN	Hex Type	All Cast Iron	NPS	DN	Black		Galv.	
							lbs	kg	lbs	kg
<p>Outside Hex Type A</p>  <p>Inside Hex Type B</p>  <p>See page 35 (Malleable Iron) for other available sizes.</p>	1½	40	A	C	¼	8	0.47	0.21	0.47	0.21
			B	C	⅜	10	0.47	0.21	0.47	0.21
			B	C	½	15	0.42	0.19	0.42	0.19
			B	C	¾	20	0.47	0.21	0.47	0.21
			A	C	1	25	0.50	0.23	0.50	0.23
	2	50	A	C	¼	8	0.75	0.34	0.75	0.34
			A	C	⅜	10	0.75	0.34	0.75	0.34
			B	C	½	15	0.70	0.32	0.70	0.32
			B	C	¾	20	0.71	0.32	0.71	0.32
			B	C	1	25	0.73	0.33	0.73	0.33
			A	C	1¼	32	0.81	0.37	0.81	0.37
	2½	65	B	C	½	15	1.28	0.58	1.28	0.58
			B	C	¾	20	1.25	0.57	1.25	0.57
			B	C	1	25	1.16	0.53	1.16	0.53
			B	C	1¼	32	1.24	0.56	1.24	0.56
			B	C	1½	40	1.29	0.59	1.29	0.59
	3	80	B	C	½	15	1.93	0.88	1.93	0.88
			B	C	¾	20	1.92	0.87	1.92	0.87
			B	C	1	25	1.90	0.86	1.90	0.86
			B	C	1¼	32	1.77	0.80	1.77	0.80
			B	C	1½	40	1.79	0.81	1.79	0.81
			A	C	2	50	1.90	0.86	1.90	0.86
			A	C	2½	65	1.63	0.74	1.63	0.74
	3½	80	B	C	1	25	2.42	1.10	2.42	1.10
B			C	1¼	32	2.56	1.16	2.56	1.16	
B			C	1½	40	2.65	1.20	2.65	1.20	
B			C	2	50	2.54	1.15	2.54	1.15	
A			C	2½	65	3.23	1.46	3.23	1.46	
A			C	3	80	1.96	0.89	1.96	0.89	

Continued on next page.

According to specifications, hex bushings and cored plugs should be used with 150# malleable iron and 125# cast iron. Solid plugs and face bushings are recommended for use with 250# and 300# fittings.

**Note:** See page 36 for pressure-temperature ratings.