

Steel Pipe Couplings

Merchant Couplings



Malleable Iron

Cast Iron

Small Steel Fittings


Pipe Nipples & Pipe Couplings

Forged Steel Fittings & Unions

Anvilets


Catawissa

J.B. Smith Products

FIGURE 346 Standard, Right & Left 	Size		Outside Diameter (Coupling)		Length		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	1/2	15	1.063	27	1 1/16	40	0.17	0.08
3/4	20	1.313	33	1 5/8	41	0.28	0.13	
1	25	1.576	40	2	51	0.43	0.20	
1 1/4	32	1.900	48	2 1/16	52	0.54	0.24	
1 1/2	40	2.200	56	2 1/16	52	0.73	0.33	
2	50	2.750	70	2 5/8	54	1.11	0.50	

Note

- The left hand threaded end of all right and left couplings is knurled for identification. All sizes of right and left couplings are taper tapped 3/4" per foot (62.5mm per meter) on the diameter and all are dipped in rust preventative.

FIGURE 347 Extra Strong (XS), Right & Left 	Size		Outside Diameter (Coupling)		Length		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	1/2	15	1.063	27	2 1/8	54	0.25	0.11
3/4	20	1.313	33	2 1/8	54	0.36	0.16	
1	25	1.576	40	2 5/8	67	0.74	0.34	
1 1/4	32	2.054	52	2 3/4	70	1.08	0.49	
1 1/2	40	2.200	56	2 3/4	70	0.95	0.43	
2	50	2.875	73	2 5/8	73	2.01	0.91	

- The left hand threaded end of all right and left couplings is knurled for identification, and all are dipped in rust preventative.
- Extra strong right and left couplings are available on request.