

EiKON™ Energy Efficient Halogen Silver PAR30

Ordering Code	Barcode	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Beam Angle	Life
35PAR30/H/FL-120V	08021	35	120	E26	CC-8	530	3.54/90	3.74/95	30	1,500
35PAR30/H/SP-120V	08022	35	120	E26	CC-8	530	3.54/90	3.74/95	15	1,500
60PAR30/H/FL-120V	08137	60	120	E26	CC-8	1070	3.54/90	3.74/95	30	1,500
60PAR30/H/NFL-120V	08138	60	120	E26	CC-8	1070	3.54/90	3.74/95	25	1,500
60PAR30/H/SP-120V	08139	60	120	E26	CC-8	1070	3.54/90	3.74/95	15	1,500

EiKON™ Energy Efficient Halogen Silver PAR30LN

Ordering Code	Barcode	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Beam Angle	Life
35PAR30LN/H/FL-120V	08023	35	120	E26	CC-8	530	4.69/119	3.74/95	30	1,500
35PAR30LN/H/NFL-120V	08024	35	120	E26	CC-8	530	4.69/119	3.74/95	25	1,500
35PAR30LN/H/SP-120V	08025	35	120	E26	CC-8	530	4.69/119	3.74/95	15	1,500
60PAR30LN/H/FL-120V	08140	60	120	E26	CC-8	1070	4.69/119	3.74/95	30	1,500
60PAR30LN/H/NFL-120V	08141	60	120	E26	CC-8	1070	4.69/119	3.74/95	25	1,500
60PAR30LN/H/SP-120V	08142	60	120	E26	CC-8	1070	4.69/119	3.74/95	15	1,500

EiKON™ Energy Efficient Halogen Silver PAR38

Ordering Code	Barcode	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Beam Angle	Life
35PAR38/H/FL-120V	08018	35	120	E26	CC-8	530	5.2/132	4.8/122	30	1,500
35PAR38/H/SP-120V	08026	35	120	E26	CC-8	530	5.2/132	4.8/122	15	1,500
35PAR38/H/WFL-120V	08027	35	120	E26	CC-8	530	5.2/132	4.8/122	50	1,500
60PAR38/H/FL-120V	08143	60	120	E26	CC-8	1070	5.2/132	4.8/122	30	1,500
60PAR38/H/SP-120V	08144	60	120	E26	CC-8	1070	5.2/132	4.8/122	15	1,500
60PAR38/H/WFL-120V	08145	60	120	E26	CC-8	1070	5.2/132	4.8/122	50	1,500
70PAR38/H/FL-120V	08187	70	120	E26	CC-8	1305	5.2/132	4.8/122	30	1,500
70PAR38/H/SP-120V	08152	70	120	E26	CC-8	1305	5.2/132	4.8/122	15	1,500
70PAR38/H/WFL-120V	08153	70	120	E26	CC-8	1305	5.2/132	4.8/122	50	1,500

EiKON™ Energy Efficient Halogen A-Line

Ordering Code	Barcode	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
29A/CL/H-120V	07757	29	120	E26	CC-8	430	4.25/108	2.36/60	1,000
43A/CL/H-120V	07758	43	120	E26	CC-8	750	4.25/108	2.36/60	1,000
53A/CL/H-120V	07759	53	120	E26	CC-8	1050	4.25/108	2.36/60	1,000
72A/CL/H-120V	07760	72	120	E26	CC-8	1490	4.25/108	2.36/60	1,000

Classic BT15 Halogen Lamps

Ordering Code	Barcode	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
60BT15/H/CL	81138	60	120	E26	CC-8	900	4.0/101	1.9/48.3	3,000
60BT15/H/W	81137	60	120	E26	CC-8	840	4.0/101	1.9/48.3	3,000
75BT15/H/W	81139	75	120	E26	CC-8	1120	4.0/101	1.9/48.3	3,000
150BT15/H/W	81141	150	120	E26	CC-8	2850	4.0/101	1.9/48.3	1,500

MR8 Halogen Lamps

Ordering Code	Barcode	Watts	Volts	Base	Filament	MOL in/mm	MOD in/mm	Beam Angle	Life
Q10MR8/NSP/CG	06240	10	6	GU4	C-8	1.56/39.5	0.99/25.2	10	2,000
Q20MR8/NFL/CG	05042	20	12	GU4	C-8	1.56/39.5	0.99/25.2	20	2,000
Q20MR8/NSP/CG	04977	20	12	GU4	C-8	1.56/39.5	0.99/25.2	10	2,000
Q35MR8/NFL/CG	06242	35	12	GU4	C-8	1.56/39.5	0.99/25.2	20	2,000

